

API SERIES DIN SERIES JIS SERIES

AYVAZ
www.ayvaz.com



You are center of our world

API SERIES
DIN SERIES
JIS SERIES

CONTENTS


API Gate Valve	01-07
API Globe Valve	08-13
API Check Valve	14-18
API Floating Ball Valve	19-22
API Trunnion Ball Valve	23-29
API Butterfly Valve	30-35

API Forged steel gate valves	36-39
API Forged steel globe valves	40-43
API Forged steel check valves	44-46

DIN Gate Valve	47-49
DIN Globe Valve	50-52
DIN Check Valve	53-56
DIN Ball Valve	57-59

JIS Gate Valve	60-63
JIS Globe Valve	64-66
JIS Check Valve	67-69
JIS Ball Valve	70-72
JIS Butterfly Valve	73-74

Steel Gate Valve



Standards

Design and Manufacture: Cast steel gate valve to API600 (ISO 10434) ; Cast stainless steel gate valve to API 603 or API 600; Forged steel gate valve to API 602. Inspection and Test: API 598.

End flange dimension: ASME B16.5 for NPS 24J; ASME B16.47 series B, ASME B16.47 series A, MSS SP-44 for NPS 24J.

BW end dimension: ASME B16.25.

Socket-weld dimension: ASME B16.11.

Face to face and end to end: ASME B16.10.

Pressure-temperature ratings: ASME B16.34.

Gasket of Cover Flange

Stainless steel + flexible graphite combined gasket is used for Class150 and Class300 gate valve; Stainless steel + flexible graphite wounded gasket is used for Class600 gate valve and ring joint gasket is also optional for Class600 gate valve; Ring Joint gasket is used for Class 900 gate valve; Pressurized seal design is used for Class1500 Class2500 gate valve.

Packing Seal

Molded flexible graphite is used for packing material. PTFE or combined packing material can be also used if being requested by the customer. The internal surface of the stuffing box, of which area is contacted with the packing, is of excellent finish ($Ra3.2\mu m$). The stem surface, contacting with the packing, should be rolled and pressed after being precisely machined, so as to reach to the high finish and compactness ($Ra0.8\mu m$) and ensure the reliable tightness of the stem area.

Back Seating Design

All our gate valves have the back seating design. In most cases, the carbon steel gate valve is fitted with a renewable back seat. For stainless steel gate valve, the back seat is machined directly in the bonnet or is machined after welding. When the gate valve is at fully open position, the sealing of the back seat can be very reliable. However, as per the requirement of API 600, it is not advisable to add or change packing by the mean of back seating when the valve is Pressure containing.

Stem Design

The stem is of integral forged design. The minimum diameter of the stem shall per the standard requirement. The connection of the stem and disc is T type. The strength of the connecting area is bigger than that of the T threaded part of the stem. The strength test of that area conforms to API 591.

Body and Bonnet Connection

The body and bonnet of Class150 ~ Class900 gate valves are usually connected with studs and nuts. And the body and bonnet of Class1500 ~ Class2500 gate valves are usually of pressure seal design.

Design of Disc

Gate Valves with NPS ≥ 2 are of wedge flexible gate;
Gate valves with NPS < 2 are of wedge solid gate.

Actuation

Hand wheel or gear box is usually used for gate valve actuation. Chain wheel and electric actuator can be also used for gate valve actuation if being requested by the customers.

Stem Nut


Usually, the stem nut is made of copper alloy. it is also can be made of ASTM A439 D2 if being requested by the customer. For large sized gate valves (NPS 10 for Class 150, NPS 8 for Class 300, NPS 6 for Class 600, NPS 5 for Class 900), rolling bearing is fitted at the two sides of the stem nut in order to minimize the open and close torque of the gate valve.

Seat

For carbon steel gate valve, the seat is usually forged steel. The sealing surface of the seat is spray welded with hard alloy specified by the customer. Renewable threaded seat is used for NPS ≤ 10 gate valves, and welded on seat can be also optional if being requested by the customer. Welded on seat is used for NPS ≤ 10 carbon steel gate valves. For Stainless steel gate valve, integral seat is usually adopted, or to weld hard alloy directly integrally. Threaded or welded on seat is also optional for stainless steel gate valve if being requested by the customer.

Belleville Spring Loaded Packing Impacting System

If being requested by the customer, the Belleville spring loaded packing impacting system can be adopted for enhancing the durability and reliability of the packing seal.



No	Part Name	No	Part Name	No	Part Name
1	Body	8	Lantern Ring	15	Gland Nut
2	Bonnet	9	Backseat Bushing	16	Pin
3	Wedge	10	Nut	17	Stem Nut
4	Seating Ring	11	Bolt	18	Retaining Nut
5	Stem	12	Gland	19	Nipple
6	Gasket	13	Gland Flange	20	H.W.Lock Nut
7	Stem Packing	14	Gland Eyebolt	21	Handwheel

API Steel Gate Valve



Trim materials			
Trim code	Seat ring surface	Wedge seat surface	Stem & backseat bushing
1	13Cr	13Cr	A182 F6a
2	18Cr-8Ni	18Cr-8Ni	A182 F304
3	25Cr-20Ni	25Cr-20Ni	A182 F310
4	Hard 13Cr	Hard 13Cr	A182 F6a
5	Stellite	Stellite	A182 F6a
6	13Cr	Cu-Ni Alloy	Monel
7	13Cr	Hard 13Cr	A182 F6a
8	Stellite	13Cr	A182 F6a
9	Cu-Ni Alloy	Cu-Ni Alloy	Monel
10	18Cr-8Ni-Mo	18Cr-8Ni-Mo	A182 F316
11	Cu-Ni Alloy	Cu-Ni Alloy	Monel
12	Stellite	18Cr-8Ni-Mo	A182 F316
13	19Cr-29Ni	19Cr-29Ni	20 Alloy

ASTM Flange Size 150 - API 500 Flange Size 150 - 24" Class Gate Valve

No	Part Name	Carbon Steel to ASTM		Stainless Steel to ASTM				Alloy Steel to ASTM		
1	Body	A216 WCB	A352 LCB	A351 CF8	A351 CF8M	A351 CF3	A351 CF3M	A217 WC6	A217 WC9	A217 C5
2	Bonnet	A216 WCB	A352 LCB	A351 CF8	A351 CF8M	A351 CF3	A351 CF3M	A217 WC6	A217 WC9	A217 C5
3	Wedge	A216 WCB	A352 LCB	A351 CF8	A351 CF8M	A351 CF3	A351 CF3M	A217 WC6	A217 WC9	A217 C5
4	Seating Ring	A105N	A350LF2	A351 CF8	A351 CF8M	A351 CF3	A351 CF3M	A182 F11	A182 F22	A182 F5
5	Stem	A182 F6a	A182 F304	A182 F304	A182 F316	A182 F304L	A182 F316L	A182 F304		
6	Gasket	Graphite+SS304, PTFE								
7	Stem Packing	Flexible Graphite								
8	Lantern Ring	A182 F6a	A182 F304	A182 F304	A182 F316	A182 F304L	A182 F316L	A182 F304		
9	Backseat Bushing	A182 F6a	A182 F304	A182 F304	A182 F316	A182 F304L	A182 F316L	A182 F304		
10	Nut	A194 2H	A194 4	A194 8				A194 7		
11	Bolt	A193 B7	A320 L7	A193 B8				A193 B16		
12	Gland	F6a	A182 F304	A182 F304	A182 F316	A182 F304L	A182 F316L	A182 F304		
13	Gland Flange	A216 WCB	A352 LCB	A351 CF8	A351 CF8	A351 CF8	A351 CF8	A217 WC6	217 WC9	A217 C5
14	Gland Eyebolt	A193 B7		A193 B8				A193 B16		
15	Gland Nut	A194 2H		A194 8				A194 7		
16	Pin	ANSI 1045		A182 F304				ANSI 1045		
17	Stem Nut	A439 D2 / B148 952A								
18	Retaining Nut	ANSI 1020								
19	Nipple	Copper Alloy								
20	H.W.Lock Nut	ANSI 1020								
21	Handwheel	A197								

※

You are center of our world

API Steel Gate Valve





Construction feature

- Bolted bonnet
- Flexible or solid wedge
- Renewable seat
- (Threaded or welded seat ring)
- ✓ 8" Yoke integral with bonnet
- △ 10" Separate yoke bolted to bonnet

API598 Pressure Test

- Pressure ratings ..Class150
- Hydraulic Shell test ..3.2MPa
- Hydraulic Seat test ..2.2MPa
- Air test ..0.6MPa



Minimum size of flange face to weight kg

Class	Size		Dimensions (mm)								Weight (Kg)	
	NPS	DN	L			d	H	H1	W	W1	Hand wheel	Gear box
			RF	RTJ	BW							
Class 150	2	50	178	191	216	51	400	-	200	-	19	-
	2 1/2	65	190	203	241	64	435	-	200	-	25	-
	3	80	203	216	283	76	515	-	250	-	33	-
	4	100	229	241	305	102	595	-	280	-	49	-
	5	125	254	267	381	127	725	-	280	-	62	-
	6	150	267	279	403	152	780	820	300	310	77	104
	8	200	292	305	419	203	975	1020	350	310	123	150
	10	250	330	343	457	254	1150	1200	400	310	188	215
	12	300	356	368	502	305	1380	1430	450	310	288	315
	14	350	381	394	572	337	1545	1580	500	310	385	435
	16	400	406	419	610	387	1733	1780	500	460	500	552
	18	450	432	445	660	438	1915	1990	500	460	601	653
	20	500	457	470	711	489	2122	2220	600	460	764	816
	24	600	508	521	813	591	2520	2600	600	460	1007	1185
	28	700	610	623	914	684	-	3050	-	600	-	1880
	30	750	610	623	914	735	-	3130	-	600	-	2300
	32	800	660	673	965	779	-	3280	-	600	-	2550
	36	900	711	724	1016	874	-	3720	-	600	-	3390
	40	1000	762	-	1066	-	-	4100	-	-	-	4880
	42	1050	787	-	1092	-	-	4300	-	-	-	5300
	48	1200	864	-	1168	-	-	5080	-	-	-	7520

API Steel Gate Valve




Construction feature

- Bolted bonnet
- Flexible or solid wedge
- Renewable seat
(Threaded or welded seat ring)
- ✓ 8" Yoke integral with bonnet
- ^ 10" Separate yoke bolted to bonnet

API598 Pressure Test

- Pressure ratings .. Class300
- Hydraulic Shell test ..7.8MPa
- Hydraulic Seat test ..5.7MPa
- Air test ..0.6MPa



Main size of outside & weight

Class	Size		Dimensions (mm)								Weight(Kg)	
	NPS	DN	L			d	H	H1	W	W1	Hand wheel	Gear box
			RF	RTJ	BW							
Class 300	2	50	216	232	216	51	420	—	200	—	25	—
	2 1/2	65	241	257	241	64	446	—	200	—	30	—
	3	80	283	298	283	76	537	—	250	—	48	—
	4	100	305	321	305	102	619	650	280	310	73	100
	5	125	381	397	381	127	722	750	300	310	99	126
	6	150	403	419	403	152	806	835	350	310	130	186
	8	200	419	435	419	203	1000	1030	400	310	208	235
	10	250	457	473	457	254	1240	1280	450	310	334	386
	12	300	502	518	502	305	1425	1460	500	310	450	502
	14	350	762	778	762	337	1585	1620	600	460	704	756
	16	400	838	854	838	387	1790	1830	500	460	923	965
	18	450	914	930	914	438	1960	2000	650	460	1131	1224
	20	500	991	1010	991	489	2158	2220	750	460	1345	1400
	24	600	1143	1165	1143	584	2576	2620	900	600	2122	2385
	28	700	1346	1372	1346	684	—	3080	—	600	—	3300
	30	750	1397	1422	1397	735	—	3180	—	600	—	3550
	32	800	1524	1553	1524	779	—	3300	—	600	—	4400
	36	900	1727	1756	1727	874	—	3760	—	600	—	6050

API SERIES

DIN SERIES

JIS SERIES

API Steel Gate Valve




Construction feature

Bolted bonnet
Flexible or solid wedge
Renewable seat
(Threaded or welded seat ring)
✓ 6" Yoke integral with bonnet
△ 8" Spigot yoke bolted to bonnet

API598 Pressure Test

Pressure ratings .. Class600
Hydraulic Shell test .. 15.6MPa
Hydraulic Seat test .. 11.4MPa
Air test .. 0.6MPa

Pressure ratings .. Class900
Hydraulic Shell test .. 23.3MPa
Hydraulic Seat test .. 17.1MPa
Air test .. 0.6MPa



Main size of outside & weight

Class	Size		Dimensions (mm)								Weight(Kg)	
	NPS	DN	L			d	H	H1	W	W1	Hand wheel	Gear box
			RF	RTJ	BW							
Class 600	2	50	292	295	292	51	444	—	200	—	32	—
	2 1/2	65	330	333	330	64	500	—	250	—	52	—
	3	80	356	359	356	76	558	585	280	310	60	87
	4	100	432	435	432	102	665	695	300	310	107	134
	5	125	508	511	508	127	760	790	350	310	175	227
	6	150	559	562	559	152	868	900	450	310	216	268
	8	200	660	664	660	200	1073	1110	500	310	399	451
	10	250	787	791	787	248	1263	1300	650	460	605	657
	12	300	838	841	838	298	1600	1650	700	460	851	893
	14	350	889	892	889	327	1705	1750	900	460	1177	1232
	16	400	991	994	991	375	1835	1900	900	460	1513	1568
	18	450	1092	1095	1092	419	—	2020	—	600	—	1980
	20	500	1194	1200	1194	464	—	2172	—	600	—	2460
	24	600	1397	1407	1397	559	—	2650	—	600	—	3650
Class 900	2	50	368	371	368	47	500	—	280	—	70	—
	2 1/2	65	419	422	419	57	550	—	280	—	110	—
	3	80	381	384	381	73	610	660	300	310	140	167
	4	100	457	460	457	98	702	750	350	310	200	227
	5	125	559	562	559	121	850	900	400	310	258	285
	6	150	610	613	610	146	980	1060	500	460	358	410
	8	200	737	740	737	190	1100	1140	650	460	550	600
	10	250	838	841	838	234	1320	1370	700	460	1000	1100
	12	300	965	968	965	282	1500	1560	900	460	1215	1310
	14	350	1029	1038	1029	311	1900	1950	900	600	1600	1700
	16	400	1130	1140	1130	354	2050	2100	900	600	2150	2330

You are center of our world

API Steel Gate Valve




Construction feature

Bolted bonnet
Flexible or solid wedge
Renewable seat
(Threaded or welded seat ring)
✓ 6" Yoke integral with bonnet
^ 8" Spigot yoke bolted to bonnet

API598 Pressure Test


Pressure ratings .. Class1500
Hydraulic Shell test .. 38.8MPa
Hydraulic Seat test .. 28.5MPa
Air test .. 0.6MPa



Main size of outside & weight

Class	Size		Dimensions (mm)								Weight(Kg)	
	NPS	DN	L			d	H	H1	W	W1	Hand wheel	Gear box
			RF	RTJ	BW							
Class 1500	2	50	368	371	368	47	510	—	280	—	70	—
	2 1/2	65	419	422	419	57	560	—	300	—	110	—
	3	80	470	473	470	70	620	670	350	310	175	202
	4	100	546	549	546	92	728	770	400	310	270	300
	5	125	673	676	673	111	870	920	450	310	378	405
	6	150	705	711	705	136	1000	1070	500	460	520	575
	8	200	832	841	832	174	1130	1180	750	460	820	915
	10	250	991	1000	991	222	1360	1410	900	600	1560	1750
	12	300	1130	1146	1130	263	—	1620	—	600	—	2120
	14	350	1257	1276	1257	289	—	2020	—	600	—	2600
	16	400	1384	1407	1384	330	—	2180	—	600	—	3450
Class 2500	2	50	451	454	451	35	530	580	280	310	100	130
	2 1/2	65	508	514	508	47	580	630	300	310	150	180
	3	80	578	584	578	57	650	700	350	310	245	275
	4	100	673	683	673	73	750	800	400	310	390	420
	5	125	794	807	794	92	900	960	500	460	550	580
	6	150	914	927	914	111	1040	1100	600	460	780	835
	8	200	1022	1038	1022	146	1150	1200	750	460	1260	1355
	10	250	1270	1292	1270	184	1400	1460	900	600	2380	2565
	12	300	1422	1445	1422	219	—	1660	—	600	—	3250

Steel Globe Valve



Standards

Design and Manufacture: Cast steel globe valve to BS 1873 and ASME B16.34; Forged steel globe valve to API 602.
Inspection and Test: API 598.
End flange dimension: ASME B16.5.
BW end dimension: ASME B16.25.
Socket-weld dimension: ASME B16.11.
Face to face and end to end: ASME B16.10.
Pressure-temperature ratings: ASME B16.34.

The features of globe valve

Bolted Bonnet; Outside Screw and Yoke; Rising stems; Metallic seating surfaces.

Body and Bonnet Connection

The body and bonnet of Class150 ~ Class900 globe valves are usually with studs and nuts. And the body and bonnet of Class1500 ~ Class2500 globe valves are usually of pressure seal design.

Gasket of Cover Flange

Stainless steel + flexible graphite wounded gasket is used for Class150 and Class300 globe valve. Stainless steel + flexible graphite wounded gasket is used for Class 600, and ring joint gasket is also optional for Class600. Ring joint gasket is used for Class900 globe valve. Pressurized seal design is used for Class 1500 ~ Class2500 globe valve.

Actuation

Hand wheel, impact hand wheel & gear box is usually used for globe valve actuation. Chain wheel and electric actuator can be also used for globe valve actuation if being requested by the customers.

Packing Seal

Molded flexible graphite is used for packing material. PTFE or combined packing material can be also used if being requested by the customer. The internal surface of the stuffing box, of which area is contacted with the packing, is of excellent finish ($Ra\ 3.2\ \mu m$). The stem surface, contacting with the packing, should be rolled and pressed after being precisely machined, so as to reach to the high finish and com-pactness ($Ra\ 0.8\ \mu m$) and ensure the reliable tightness of the stem area.

Belleville Spring Loaded Packing Impacting System

If being requested by the customer, the Belleville spring loaded packing impacting can be adopted for enhancing the durability and reliability of the packing seal.

◎ Back Seating Design

All our globe valves have the back seat design. In most cases, the carbon steel globe valve is fitted with a renewable back seat. For stainless steel globe valve, the back seat is machined directly in the bonnet or is machined after welding. When the globe valve is at fully open position, the sealing of the back seat can be very reliable. However, as per the requirement of API, it is not advisable to add or change packing by the mean of back seating when the valve is pressure containing.

◎ Seat


For carbon steel globe valve, the seat is usually forged steel. The sealing surface of the seat is spray welded with hard alloy specified by the customer. Renewable threaded seat is used for NPS ≤ 10 globe valve and welded on seat can be also optional if being requested by the customer. Welded on seat is used for NPS ≥ 12 carbon steel globe valves. For stainless steel globe valve, integral seat is usually adopted, or to weld hard alloy directly integrally. Threaded or welded on seat is also optional for stainless steel globe valve if being requested by the customer.

◎ Stem Design

The stem is of integral forged design. The minimum diameter of the stem shall per the standard requirement.

◎ Stem Nut

Usually, the stem nut is copper alloy. It is also can be made of ASTM A439 D2 if being requested by the customer. For large sized globe valve, rolling bearing is fitted at the two sides of stem nut in order to minimize the open and close torque of the globe valve.



No	Part Name	No	Part Name	No	Part Name
1	Body	10	Lantern Ring	19	Gland Nut
2	Bonnet	11	Thrust Washer	20	Pin
3	Disc	12	Nut	21	Stem Nut
4	Seating Ring	13	Bolt	22	Bearing
5	Gasket	14	Anti-rotating Device	23	Retaining Nut
6	Stem	15	Screw	24	Nipple
7	Disc Nut	16	Gland	25	Bevel gearbox
8	Backseat Bushing	17	Gland Flange		
9	Stem Packing	18	Gland Eyebolt		

API Steel Globe Valve



API SERIES

DIN SERIES

JIS SERIES



Trim material			
Trim code	Seat ring surface	Wedge seat surface	Stem & backseat bushing
1	13Cr	13Cr	A182 F6a
2	18Cr-8Ni	18Cr-8Ni	A182 F304
3	25Cr-20Ni	25Cr-20Ni	A182 F310
4	Hard 13Cr	Hard 13Cr	A182 F6a
5	Stellite	Stellite	A182 F6a
6	13Cr	Cu-Ni Alloy	Monel
7	13Cr	Hard 13Cr	A182 F6a
8	Stellite	13Cr	A182 F6a
9	Cu-Ni Alloy	Cu-Ni Alloy	Monel
10	18Cr-8Ni-Mo	18Cr-8Ni-Mo	A182 F316
11	Cu-Ni Alloy	Cu-Ni Alloy	Monel
12	Stellite	18Cr-8Ni-Mo	A182 F316
13	19Cr-29Ni	19Cr-29Ni	20 Alloy

ASTM Material for 653 #77 Class Steel Globe Valve

No	Part Name	Carbon Steel to ASTM		Stainless Steel to ASTM				Alloy Steel to ASTM		
1	Body	A216 WCB	A352 LCB	A351 CF8	A351 CF8M	A351 CF3	A351 CF3M	A217 WC6	A217 WC9	A217 C5
2	Bonnet	A216 WCB	A352 LCB	A351 CF8	A351 CF8M	A351 CF3	A351 CF3M	A217 WC6	A217 WC9	A217 C5
3	Disc	A216 WCB	A352 LCB	A351 CF8	A351 CF8M	A351 CF3	A351 CF3M	A217 WC6	A217 WC9	A217 C5
4	Seating Ring	A105N	A350LF2	A351 CF8	A351 CF8M	A351 CF3	A351 CF3M	A182 F11	A182 F22	A182 F5
5	Gasket	Graphite+SS304, PTFE								
6	Stem	A182 F6a	A182 F304	A182 F304	A182 F316	A182 F304L	A182 F316L	A182 F304		
7	Disc Nut	A182 F6a	A182 F304	A182 F304	A182 F316	A182 F304L	A182 F316L	A182 F304		
8	Backseat Bushing	A182 F6a	A182 F304	A182 F304	A182 F316	A182 F304L	A182 F316L	A182 F304		
9	Stem Packing	Flexible Graphite								
10	Lantern Ring	A182 F6a	A182 F304	A182 F304	A182 F316	A182 F304L	A182 F316L	A182 F304		
11	Thrust Washer	A182 F6a	A182 F304	A182 F304	A182 F316	A182 F304L	A182 F316L	A182 F304		
12	Nut	A194 2H	A194 4	A194 8				A194 7		
13	Bolt	A193 B7	A320 L7	A193 B8				A193 B16		
14	Anti-rotating Device	ANSI 1020		A182 F304				ANSI 1020		
15	Gland	A194 2H		A194 8				A194 2H		
16	Screw	F6a	A182 F304	A182 F304	A182 F316	A182 F304L	A182 F316L	A182 F304		
17	Gland Flange	A216 WCB	A352 LCB	A351 CF8	A351 CF8	A351 CF8	A351 CF8	A217 WC6	A217 WC9	A217 C5
18	Gland Eyebolt	A193 B7		A193 B8				A193 B16		
19	Gland Nut	A194 2H		A194 8				A194 7		
20	Pin	ANSI 1045		A182 F304				ANSI 1045		
21	Stem Nut	A439 D2/ B148 952A								
22	Bearing	/								
23	Retaining Nut	ANSI 1020								
24	Nipple	Copper Alloy								
25	Bevel gearbox	/								

You are center of our world

API Steel Globe Valve





Construction feature

Bolted bonnet
Flat or plug type disc
Renewable seat
(Threaded or welded seat ring)
Λ 10° Thrust bearing design

API598 Pressure Test

Pressure ratings .. Class150
Hydraulic Shell test ..3.2MPa
Hydraulic Seat test ..2.2MPa
Air test ..0.6MPa



Class	Size		Dimensions (mm)								Weight (Kg)	
	NPS	DN	L			d	H	H1	W	W1	H.W	G.O
			RF	RTJ	BW							
Class 150	2	50	203	216	203	51	330	-	200	-	19	-
	2 1/2	65	216	229	216	64	360	-	250	-	27	-
	3	80	241	254	241	76	390	-	280	-	36	-
	4	100	292	305	292	102	445	-	300	-	53	-
	5	125	356	369	356	127	480	-	350	-	75	-
	6	150	406	419	406	152	520	556	350	310	94	126
	8	200	495	508	495	203	600	658	400	310	148	180
	10	250	622	635	622	254	773	805	450	460	242	291
	12	300	698	711	698	305	880	955	500	460	438	480
	14	350	787	800	787	337	950	1100	600	460	-	600
	16	400	914	927	914	387	996	1175	600	460	-	850
	20	500	978	991	978	488	-	1450	-	600	-	1650
	24	600	1295	1308	1295	590	-	1690	-	600	-	2200

API SERIES

DIN SERIES

JIS SERIES

API Steel Globe Valve




Construction feature

Bolted bonnet
Flat or plug type disc
Renewable seat
(Threaded or welded seat ring)
Λ 10" Thrust bearing design

API598 Pressure Test

Pressure ratings ..Class300
Hydraulic Shell test ..7.8MPa
Hydraulic Seat test ..5.7MPa
Air test ..0.6MPa



Main size of outside & weight

Class	Size		Dimensions (mm)								Weight (Kg)	
	NPS	DN	L			d	H	H1	W	W1	H.W	G.O
			RF	RTJ	BW							
Class 300	2	50	267	283	267	51	385	—	200	—	25	—
	2 1/2	65	292	308	292	64	420	—	200	—	42	—
	3	80	318	333	318	76	440	—	280	—	46	—
	4	100	356	371	356	102	515	—	350	—	74	—
	5	125	400	416	400	127	580	—	350	—	111	—
	6	150	444	460	444	152	660	690	400	310	165	195
	8	200	559	575	559	203	900	950	550	460	275	327
	10	250	622	638	622	254	950	990	600	460	400	452
	12	300	711	727	711	305	1030	1080	700	460	624	725
	14	350	762	854	762	337	1130	1155	—	600	—	880
	16	400	864	879	864	387	1310	1325	—	600	—	1300
	18	450	977	—	977	431	—	1473	—	720	—	1600
	20	500	1016	—	1016	482	—	1574	—	720	—	2100

API Steel Globe Valve




Construction feature

Bolted bonnet
Flat or plug type disc
Renewable seat
(Threaded or welded seat ring)
Λ 6" Thrust bearing design

API598 Pressure Test

Pressure ratings ..Class600
Hydraulic Shell test ..15.6MPa
Hydraulic Seat test ..11.4MPa
Air test ..0.6MPa

Pressure ratings ..Class900
Hydraulic Shell test ..23.3MPa
Hydraulic Seat test ..17.1MPa
Air test ..0.6MPa




Main size of outside & weight

Class	Size		Dimensions (mm)								Weight (Kg)	
	NPS	DN	L			d	H	H1	W	W1	H.W	G.O
			RF	RTJ	BW							
Class 600	2	50	292	295	292	51	360	-	250	-	32	-
	2 1/2	65	330	333	330	64	410	-	280	-	42	-
	3	80	356	359	356	76	465	-	300	-	63	-
	4	100	432	435	432	102	545	575	400	310	107	138
	5	125	508	511	508	127	625	660	500	310	185	215
	6	150	559	562	559	152	785	820	550	460	290	342
	8	200	660	664	660	200	930	960	650	460	540	645
Class 900	2	50	368	371	368	47	480	-	350	-	55	-
	2 1/2	65	419	422	419	57	520	-	350	-	68	-
	3	80	381	384	381	73	564	630	400	310	95	128
	4	100	457	460	457	98	685	720	450	310	160	210
	5	125	559	562	559	121	780	840	550	460	270	325
	6	150	610	613	610	146	950	1015	650	460	410	480

Class	DN		RTJ							
	mm	in	L	D	D1	D2	b	n-φd	H	D0
Class 1500	65	2 1/2	422	244	190.5	108.0	49.0	8-φ28.5	461	400
	80	3	473	267	203.2	136.5	55.7	8-φ32	554	450
	100	4	549	311	241.3	161.9	61.8	8-φ35	639	500
	125	5	676	375	292.1	193.7	81.1	8-φ41	780	560
	150	6	711	394	317.5	211.1	92.1	12-φ38	904	630
	200	8	841	483	393.7	269.9	103.0	12-φ44.5	1140	680

Steel Check Valve



◎ **Reliable seat seal**

Design and Manufacture: Cast steel check valve to BS1868, ASME B16.34 and API 6D;
Forged steel check valve to API 602.
Inspection and Test: API 598.
End flange dimension: ASME B16.5Jfor NPS $\leq$ 24JJ
ASME B 16.47 series B, ASME B16.47 series A,
MSS SP-44Jfor NPSJ24J.
BW end dimension: ASME B16.25.
Socket-weld dimension: ASME B16.11.
Face to face and end to end: ASME B16.10.
Pressure-temperature ratings: ASME B16.34.

◎ **Seat**

For carbon steel check valve, the seat is usually forged Steel. The sealing surface of the seat is spray welded with hard alloy Specified by the customer. Renewable threaded seat is used for NPS $\leq$ 10 check valves, and welded on seat can be also optional if being requested by the customer. Welded on seat is used for NPS $\geq$ 12 carbon steel check valves. For stainless steel check Valve, integral seat is usually adopted, or to weld hard alloy directly integrally. Threaded or welded on seat is also optional for stainless steel check valve if being requested by the customer.

◎ **The features of check valve**

Bolted Bonnet;
Swing and lift disc;
Metallic seating surfaces.


◎ **Body-To-Bonnet Joint**

Stainless steel + flexible graphite wounded gasket is used for Class150 and Class300 check valve; Stainless steel + flexible graphite wounded gasket is used for Class600 check valve, and joint gasket is also optional for Class600 check valve; Ring joint gasket is used for Class900 check valve; Pressure seal design is used for Class1500 ~ Class2500 check valves.

◎ **Body and Bonnet Connection**

The body and bonnet of Class150~Class900 check valves are usually with studs and nuts. And the body and bonnet of Class1500 ~ Class2500 check valves are usually of pressure seal design.

API Steel Check Valve



No	Part Name	No	Part Name	No	Part Name
1	Body	6	Yoke	11	Nut
2	Cover	7	Gasket	12	Bolt
3	Seat Ring	8	Disc Washer	13	Screw
4	Disc	9	Disc Nut	14	Lifting Lug
5	Hinge	10	Pin		

API SERIES

DIN SERIES

JIS SERIES

API Steel Check Valve



API SERIES

DIN SERIES

JIS SERIES



Trim material			
Trim code	Seat ring surface	Wedge seat surface	Hinge Pin
1	13Cr	13Cr	A182 F6a
2	18Cr-8Ni	18Cr-8Ni	A182 F304
3	25Cr-20Ni	25Cr-20Ni	A182 F310
4	Hard 13Cr	Hard 13Cr	A182 F6a
5	Stellite	Stellite	A182 F6a
6	13Cr	Cu-Ni Alloy	Monel
7	13Cr	Hard 13Cr	A182 F6a
8	Stellite	13Cr	A182 F6a
9	Cu-Ni Alloy	Cu-Ni Alloy	Monel
10	18Cr-8Ni-Mo	18Cr-8Ni-Mo	A182 F316
11	Cu-Ni Alloy	Cu-Ni Alloy	Monel
12	Stellite	18Cr-8Ni-Mo	A182 F316
13	19Cr-29Ni	19Cr-29Ni	20 Alloy

ASTM Material List of API 5000 Swing Check Valve

No.	Part name	Carbon Steel to ASTM		Stainless Steel to ASTM				Alloy Steel to ASTM		
1	Body	A216 WCB	A352 LCB	A351 CF8	A351 CF8M	A351 CF3	A351 CF3M	A217 WC6	A217 WC9	A217 C5
2	Cover	A216 WCB	A352 LCB	A351 CF8	A351 CF8M	A351 CF3	A351 CF3M	A217 WC6	A217 WC9	A217 C5
3	Seat Ring	A105N	A352 LF2	A351 CF8	A351 CF8M	A351 CF3	A351 CF3M	A182 F11	A182 F22	A182 F5
4	Disc	A216 WCB	A352 LCB	A351 CF8	A351 CF8M	A351 CF3	A351 CF3M	A217 WC6	A217 WC9	A217 C5
5	Hinge	A216 WCB	A352 LCB	A351 CF8	A351 CF8M	A351 CF3	A351 CF3M	A217 WC6	A217 WC9	A217 C5
6	Yoke	A216 WCB	A352 LCB	A351 CF8	A351 CF8M	A351 CF3	A351 CF3M	A217 WC6	A217 WC9	A217 C5
7	Gasket	Graphite+SS304, PTFE								
8	Disc Washer	A182 F6a	A182 F6a	A182 F304	A182 F316	A182 F304L	A182 F316L	A182 F304		
9	Disc Nut	A182 F6a	A182 F304	A182 F304	A182 F316	A182 F304L	A182 F316L	A182 F304		
10	Pin	A182 F6a	A182 F304	A182 F304	A182 F316	A182 F304L	A182 F316L	A182 F304		
11	Nut	A194 2H	A194 4	A194 8				A194 7		
12	Bolt	A193 B7	A320 L7	A193 B8				A193 B16		
13	Screw	193 B7	A320 L7	A182 F304	A182 F316	A182 F304L	A182 F316L	A193 B16		
14	Lifting Lug	A194 2H								

※

You are center of our world

API Steel Swing Check Valve




Construction feature

Bolted cover
Renewable seat
(Threaded or welded seat ring)

API598 Pressure Test

Pressure ratings: Class150
Hydraulic Shell test: 3.2MPa
Hydraulic Seat test: 2.2MPa
Air test: 0.6MPa

Pressure ratings: Class300
Hydraulic Shell test: 7.8MPa
Hydraulic Seat test: 5.7MPa
Air test: 0.6MPa



Size		Class 150						Class 300					
NPS	DN	L			d	H	Weight (Kg)	L			d	H	Weight (Kg)
		RF	RTJ	BW				RF	RTJ	BW			
2	50	203	216	203	51	132	15	267	283	267	51	144	20
2 1/2	65	216	229	216	64	147	20	292	308	292	64	169	35
3	80	241	254	241	76	176	27	318	333	318	76	210	40
4	100	292	305	292	102	198	45	356	371	356	102	260	61
5	125	330	343	330	127	255	58	400	416	400	127	295	80
6	150	356	368	356	152	320	69	445	460	445	152	326	130
8	200	495	508	495	203	380	131	533	549	533	203	380	190
10	250	622	635	622	254	440	219	622	638	622	254	440	296
12	300	699	711	699	305	480	321	711	727	711	305	520	450
14	350	787	800	787	337	530	380	838	854	838	337	540	640
16	400	864	876	864	387	580	560	864	879	864	387	588	850
18	450	978	991	978	438	618	630	978	994	978	432	670	1030
20	500	978	991	978	489	657	770	1016	1035	1016	483	720	1330
24	600	1295	1308	1295	591	760	960	1346	1368	1346	584	850	1950
26	650	1295	-	1295	633	840	1250	1346	1372	1346	633	920	2300
28	700	1448	-	1448	684	920	1580	1499	1524	1499	684	1150	2600
30	750	1524	1537	1524	735	980	1950	1594	1619	1594	735	1260	3200
32	800	1727	-	1727	779	1016	2800	1727	-	1727	779	1380	3700
36	900	1956	1969	1956	874	1092	3200	2083	-	2083	874	1540	4300

API SERIES

DIN SERIES

JIS SERIES

API Steel Swing Check Valve



Construction feature


Bolted cover
Renewable seat
(Threaded or welded seat ring)

API598 Pressure Test

Pressure ratings: Class600
Hydraulic Shell test: 15.6MPa
Hydraulic Seat test: 11.4MPa
Air test: 0.6MPa

Pressure ratings: Class900
Hydraulic Shell test: 23.3MPa,
Hydraulic Seat test: 17.1MPa,
Air test: 0.6MPa

Pressure ratings: 1500
Hydraulic Shell test: 38.8MPa
Hydraulic Seat test: 28.5MPa
Air test: 0.6MPa




Main size of outside & weight

Size		Class 600						Class 900					
NPS	DN	L			d	H	Weight (Kg)	L			d	H	Weight (Kg)
		RF	RTJ	BW				RF	RTJ	BW			
2	50	292	295	292	51	170	28	368	371	368	47	200	48
2 1/2	65	330	333	330	64	178	40	419	422	419	57	220	75
3	80	356	359	356	76	246	68	381	384	381	73	280	95
4	100	432	435	432	102	290	117	457	460	457	98	320	135
5	125	508	511	508	127	320	155	559	562	559	121	360	200
6	150	559	562	559	152	360	192	610	613	610	146	400	264
8	200	660	664	660	200	430	340	737	740	737	190	480	424
10	250	787	791	787	248	502	515	838	841	838	234	560	730
12	300	838	841	838	298	554	750	965	968	965	282	632	1070
14	350	889	892	889	327	595	890	1029	1038	1029	311	680	1180
16	400	991	994	991	375	680	1303	1130	1140	1130	354	780	1790
18	450	1092	1095	1092	419	778	1800	1219	1232	1219	400	880	2500
20	500	1194	1200	1194	464	970	2150	1321	1334	1321	444	1050	3080
24	600	1397	1407	1397	559	1100	3200	1549	1568	1549	533	1200	4600

Size		Class 1500						Class 2500					
NPS	DN	L			d	H	Weight (Kg)	L			d	H	Weight (Kg)
		RF	RTJ	BW				RF	RTJ	BW			
2	50	368	371	368	47	210	48	451	454	451	35	230	68
2 1/2	65	419	422	419	57	240	75	508	514	508	47	260	100
3	80	470	473	470	70	303	120	578	584	578	57	330	165
4	100	546	549	546	92	340	180	673	683	673	73	370	260
5	125	673	676	673	111	380	294	794	807	794	92	410	440
6	150	705	711	705	136	430	385	914	927	914	111	460	580
8	200	832	841	832	174	500	634	1022	1038	1022	146	530	970
10	250	991	1000	991	222	590	1140	1270	1292	1270	184	620	1700
12	300	1130	1146	1130	263	660	1650	1422	1445	1422	219	690	2600
14	350	1257	1276	1257	289	710	2000	-	-	-	-	-	-
16	400	1384	1407	1384	330	820	2700	-	-	-	-	-	-

You are center of our world

Floating Ball Valve




Standards


Design and Manufacture: API 6D, BS5351, ASME B16.34
API 608, MSS-SP-72
Face To Face Dimension: ASME B16.10
Flange Connection Dimension: ASME B16.5
BW Connection Dimension: ASME B16.25
Test And Inspection: API 598
Fire-safe Design: API 607
Anti-static Design&Anti Blow-out Stem

Application

Floating ball valves are suitable for various kinds of pipelines of Class 150 to Class 600, to turn on or off the pipeline medium, of which the operation types include manual, worm gear and pneumatic or electric actuators.



At lower medium pressure




At higher medium pressure

Reliable seat seal

The structure design of elastic sealing ring has been adopted for floating ball valves. This seat design features a bigger sealing pressure ratio between the ring surface and the ball when medium pressure gets lower, where the contacting area is smaller. Thus, the reliable seal is ensured. When the medium pressure gets higher, the contacting area between seat ring and ball becomes bigger as the sealing ring transforms elastically to undertake the bigger force pushed by the medium without any damage.

Anti-static feature

The traditional packing flange design has been improved to be of two piece structure, i.e., being as a packing flange plate and a follower, the latter contacts the flange plate with spherical surface. Thus, the follower remains vertical always, and is lined internally with a PTFE bush to prevent the galling against and friction between the stem, which can also reduce the operation torque of the valve.




Anti-Static design for ball valve $\geq 32\text{mm}$ Anti-Static design for ball valve $\leq 25\text{mm}$

API Floating Ball Valve




Fire safe design


With the valve heated in a fire application, the non-metal material parts such as seat sealing ring of PTFE, stem back seat gasket, gland packing, and the sealing gasket between body and bonnet might disintegrate or be damaged due to high temperature. Our company specially designed structure of auxiliary metal to metal seal is provided to effectively prevent both internal and external leakage of the valve. As required by customers, Our company floating ball valves with design can meet the requirement of API 607.



Fire safe design of seat




Before fire



After fire


Fire safe design of stem



Fire safe design of valve body and bonnet flanges


Mounting pad provided

Our company has provided for floating ball valve with a mounting pad, through which it is easy to fix the actuators, such as worm gear, pneumatic and electric actuators.




Reliable stem seal

The blow-out proof design has been adopted for the stem to ensure that even if the pressure in the body cavity is risen accidentally and the packing flange becomes invalid, the stem may not be blown out by medium. The stem features the design with a backseat, being assembled from underneath. The sealing force against the backseat gets higher as the medium pressure becomes higher. So the reliable seal of the stem can be assured under variable medium pressure.




Stem assembled from underneath may not be blown out by medium




Stem assembled downward may be blown out

V type packing structure has been employed to effectively transform the pushing force of the gland flange and the medium pressure into the sealing force against the stem.




Packing before pressed



Packing after pressed

Wrong operation prevention

To prevent the ball valve from wrong operation, the keylock with 90° of open and close positioning pad has been provided, which can be lockable as required. At the stem head, where the lever fixes, a flat is designed so that the valve opens with the lever in parallel to piping, and with the lever right-angled to the piping, the valve is closed. So, it is ensured that the valve indicator of open and close can never make mistake.



API Floating Ball Valve



ASTM Material list of Floating ball valve


No	Part Name	Carbon Steel to ASTM		Stainless Steel to ASTM			
1	Body	A216 WCB	A352 LCB	A351 CF8	A351 CF8M	A351 CF3	A351 CF3M
2	Bonnet	A216 WCB	A352 LCB	A351 CF8	A351 CF8M	A351 CF3	A351 CF3M
3	Ball	A351 CF8	A352 LCB	A351 CF8	A351 CF8M	A351 CF3	A351 CF3M
4	Stem	A182 F6a	A182 F304	A182 F304	A182 F316	A182 F304L	A182 F316L
5	Seat ring	PTFE, RTFE, PEEK, DELRIN					
6	Gasket	Graphite+SS304, PTFE					
7	O-ring	Fluororubber					
8	Bolt	A193 B7/B7M	A193 L7/L7M	A193 B8/B8M			
9	Nut	A194 2H/2HM	A194 4/4M	194 8/8M			
10	Small spring	SS304					
11	Small ball	SS304					
12	Thrust washer	PTFE					
13	Stem packing	Flexible Graphite/PTFE					
14	Packing gland	A216 WCB	A352 LCB	A351 CF8	A351 CF8M	A351 CF3	A351 CF8M
15	Shaft sleeve	PTFE					
16	Screw	A193 B7	A320 L7	A193 B8/B8M			
17	Positioning plate	Galvanized Steel					
18	Retaining ring	Carbon Steel					
19	Lever	Carbon Steel					
20	Gasket	Carbon Steel					
21	Screw	Carbon Steel					

API SERIES

DIN SERIES

JIS SERIES

API Floating Ball Valve



API SERIES

DIN SERIES

JIS SERIES

Main size of outside & weight

150Lb

Size	in	1/2	3/4	1	1 1/2	2	2 1/2	3	4	6	8	10	12
	mm	15	20	25	40	50	65	80	100	150	200	250	300
L (RF)	in	4.25	4.62	5.00	6.50	7.00	7.50	8.00	9.00	15.50	18.00	21.00	24.00
	mm	108	117	127	165	178	190	203	229	394	457	533	610
L1 (BW)	in	5.50	6.00	6.50	7.50	8.50	9.50	11.12	12.00	18.00	20.50	22.00	25.00
	mm	140	152	165	190	216	241	283	305	457	521	559	635
H	in	2.12	2.12	2.75	3.50	4.12	6.12	7.25	8.00	10.00	11.00	13.50	16.50
	mm	55	55	70	90	105	155	185	205	255	280	345	420
WT (Kg)	RF	2.3	3	4.5	7	9.5	15	19	33	93	160	200	280
	BW	1.8	2.8	3.7	6.2	8.5	14	21	35	98	170	225	295

Main size of outside & weight

300Lb

Size	in	1/2	3/4	1	1 1/2	2	2 1/2	3	4	6	8	10	12
	mm	15	20	25	40	50	65	80	100	150	200	250	300
L (RF)	in	5.50	6.00	6.50	7.50	8.50	9.50	11.12	12.00	15.88	19.75	22.38	25.50
	mm	140	152	165	190	216	241	283	305	403	502	568	648
L1 (BW)	in	5.50	6.00	6.50	7.50	8.50	9.50	11.12	12.00	18.00	20.50	22.00	25.00
	mm	140	152	165	190	216	241	283	305	457	521	559	635
H	in	2.12	2.12	2.75	3.50	4.12	6.12	7.25	8.00	10.00	11.00	13.50	16.50
	mm	55	55	70	90	105	153	187	206	255	280	345	420
WT (Kg)	RF	2.5	3.5	5.5	10.5	14.5	23.5	30	55	118	200	250	330
	BW	1.8	2	3.2	5.5	8.7	15	18	36	85	152	182	232

Main size of outside & weight

600Lb

Size	in	1/2	3/4	1	1 1/2	2	2 1/2	3	4
	mm	15	20	25	40	50	65	80	100
L/L1 (RF/BW)	in	6.50	7.50	8.50	9.50	11.50	13.00	14.00	17.00
	mm	165	190	216	241	292	330	356	432
L2 (RTJ)	in	-	-	-	-	11.62	13.12	14.12	17.12
	mm	-	-	-	-	295	333	359	435
H	in	2.38	2.38	3.00	4.00	4.75	6.88	8.38	9.25
	mm	61.5	61.5	78	101	120	174	212	234
WT (Kg)	RF/RTJ	3.3	4.5	7.2	13.5	19	31	39	71
	BW	2.6	3.1	4.8	8	13	22	27	53

You are center of our world

Trunnion Ball Valve



Standards

Design and Manufacture: API 6D, BS5351, ASME B16.34
API 608, MSS-SP-72

Face To Face Dimension: ASME B16.10

End flange dimension: ASME B16.5(for NPS 24); ASME B16.47 series B, ASME B16.47 series A, MSS SP-44(for NPS 24).

BW Connection Dimension: ASME B16.25


Test And Inspection: API 598

Fire-safe Design: API 607

Anti-static Design&Anti Blow-out Stem


Urgent grease injection device

According to customers' requirement, the trunnion ball valves made by Our company are provided with devices for urgent grease injection, which are on both the stem and seat for the trunnion ball valves of DN>150mm (NPS6), and in the body cavity for the valve of DN<125mm. When the O ring of stem or the body seat ring is damaged due to accident, the medium leakage between body and stem can be prevented by injecting the sealing grease through the device.



Double-block and bleed functions

In TEK valve company, trunnion ball valve features the front ball sealing design structure. Each seat of the ball valve can separately cut off the medium at both inlet and outlet of the valve to realize double-block functions. When the ball valve is closed, body cavity and two of the body ends can be blocked with each other even if both the inlet and outlet are under pressure, when the medium left in the body cavity might be bled through the relief valve.



Blow-out proof stem

Blow-out proof structure is provided with for the stem, which is positioned by the up-end cap and screw, being guaranteed not to be blown-out by the medium even if at abnormal risen pressure in the cavity.

API Trunnion Ball Valve




API SERIES

DIN SERIES

JIS SERIES

Anti-static design

The ball of the trunnion ball valve gets close contact with each other through the trunnion, adjusting cushion, and down-end cap, the passage of static electricity thus forms together with the valve, which may lead the static electricity caused by sparks generated by friction between the ball and seat during on and off performance to the ground to prevent the possible risk of fire or explosion.




The Bi-sealing design structure, i.e. seat sealing in front of the ball and seat sealing behind the ball

According to some special working conditions and customers' requirement, We has provided the trunnion ball valve with the Bi-sealing design structure, i.e. seat sealing in front of the ball and seat sealing behind the ball, thus the reliable sealing of the valve is ensured because the valve can perform normally even if one of the effective sealing designs becomes lost due to the abnormal condition.


Regarding the seat in front of the ball, the piston effect formed by the area difference between D_1 and D_2 , plus the pre-tightened force of a spring would cause the seat in front of the ball by the pressure difference of the medium before and after the valve to touch the ball closely to form the tightness, of which the sealing force will become bigger as the pressure difference gets higher.

Regarding the seat after the ball, the piston effect formed by the area difference between D_2 and D_3 , plus the pretig-htened force of a spring would cause the seat behind the ball to touch the ball closely to form the tightness, of which the sealing force will become bigger as the pressure difference gets higher.




Self-relief in the body cavity

As the liquid medium left in the body cavity gasifies due to increased temperature, the pressure in the body cavity becomes abnormally higher when the medium itself in the cavity would propel the seat and self-relieves the pressure to ensure the safety of valve.




Fire safe design

With the valve heated in a fire application, the non-metal material parts such as seat sealing ring of PTFE, O ring for the stem, and sealing gasket for body and bonnet, might be damaged due to high temperature. Our company special design of auxiliary metal to metal or the graphite seal is provided for the trunnion ball valve to effectively prevent both internal and external leakage of the valve. As required by customers, Our company fire safe design for the trunnion ball valve meets the requirement of API 607, API 6Fa, BS 6755.



Fire safe design of seat




Fire safe design of valve body and bonnet flanges

Fire safe design of stem

Mounting pad provided

Our company has provided for trunnion ball valve with a mounting pad for fixing the actuators, such as worm gear, pneumatic, electric, hydraulic, and pneumatic & hydraulic actuators.

API Cast Steel Trunnion Ball Valve



Main size of outside & weight

150Lb

Size	in	2	2 1/2	3	4	6	8	10	12	14	16	18	20	24	26	28	30	32	36
	mm	50	65	80	100	150	200	250	300	350	400	450	500	600	650	700	750	800	900
L (RF)	in	7.00	7.50	8.00	9.00	15.50	18.00	21.00	24.00	27.00	30.00	34.00	36.00	42.00	45.00	49.00	51.00	54.00	60.00
	mm	178	190	203	229	394	457	533	610	686	762	864	914	1067	1143	1245	1295	1372	1524
L1 (BW)	in	8.50	9.50	11.12	12.00	18.00	20.50	22.00	25.00	30.00	33.00	36.00	39.00	45.00	49.00	53.00	55.00	60.00	68.00
	mm	216	241	283	305	457	521	559	635	762	838	914	991	1143	1245	1346	1397	1524	1727
H	in	7.00	7.50	8.25	9.25	20.88	24.62	25.62	30.75	31.00	36.25	38.25	43.38	5.25	50.75	55.12	64.12	70.88	80.75
	mm	177	190	210	235	530	625	650	780	790	920	970	1100	1150	1290	1400	1630	1840	2050
W	in	14	16	20	20	24	24	24	24	32	32	32	32	32	32	32	32	32	32
	mm	350	400	500	500	600	600	600	600	800	800	800	800	800	800	800	800	800	800
WT (Kg)	RF	15	19	27	38	81	140	160	205	260	390	510	750	1200	1400	1860	2100	2530	2970
	BW	13.5	15.5	24.5	32.5	76	132	147	182	241	370	495	726	1125	1250	1640	1930	2390	2760

Main size of outside & weight

300Lb

Size	in	2	2 1/2	3	4	6	8	10	12	14	16	18	20	24	26	28	30	32	36
	mm	50	65	80	100	150	200	250	300	350	400	450	500	600	650	700	750	800	900
L (RF)	in	8.50	9.50	11.12	12.00	15.88	19.75	22.38	25.50	30.00	33.00	36.00	39.00	45.00	49.00	53.00	55.00	60.00	-
	mm	216	241	283	305	403	502	568	648	762	838	914	991	1143	1245	1346	1397	1524	-
L1 (BW)	in	8.50	9.50	11.12	12.00	18.00	20.50	22.00	25.00	30.00	33.00	36.00	39.00	45.00	49.00	53.00	55.00	60.00	-
	mm	216	241	283	305	403	521	559	635	762	838	914	991	1143	1245	1346	1397	1524	-
H	in	7.00	7.50	8.25	9.25	20.88	24.62	25.62	30.75	31.00	36.25	38.25	43.38	45.25	50.75	55.12	64.12	70.88	-
	mm	177	190	210	235	530	625	650	780	790	920	970	1100	1150	1290	1400	1630	1800	-
W	in	14	16	20	20	24	24	24	24	32	32	32	32	32	32	32	32	32	-
	mm	350	400	500	500	600	600	600	600	800	800	800	800	800	800	800	800	800	-
WT (Kg)	RF	19	24	34	48	101	175	200	255	325	485	635	935	1500	1750	2225	2450	2870	-
	BW	14	16	25	34	82	145	155	185	238	375	516	782	1280	1375	1825	2180	2260	-

API SERIES

DIN SERIES

JIS SERIES

API Cast Steel Trunnion Ball Valve



API SERIES

Main size of outside & weight															600Lb	
Size	in	2	2 1/2	3	4	6	8	10	12	14	16	18	20	24	26	28
	mm	50	65	80	100	150	200	250	300	350	400	450	500	600	650	700
L/L1 (RF/BW)	in	11.50	13.00	14.00	17.00	22.00	26.00	31.00	33.00	35.00	39.00	43.00	47.00	55.00	57.00	61.00
	mm	292	330	356	432	559	660	787	838	889	991	1092	1194	1397	1448	1549
L2 (RTJ)	in	11.62	13.12	14.12	17.12	22.12	26.12	31.12	33.12	35.12	39.12	43.12	47.25	55.38	57.50	61.50
	mm	295	333	359	435	562	664	791	841	892	994	1095	1200	1407	1461	1562
H	in	7.12	7.62	8.50	9.50	21.52	25.00	26.12	31.12	31.88	36.38	38.75	44.50	46.62	52.50	57.00
	mm	180	193	215	241	540	635	665	790	810	925	985	1130	1185	1335	1450
W	in	14	16	20	20	24	24	24	24	32	32	32	32	32	32	32
	mm	350	400	500	500	600	600	600	600	800	800	800	800	800	800	800
WT (Kg)	RF/RTJ	26	35	58	81	142	287	540	780	1000	1300	1700	2100	3400	3800	4500
	BW	19	25	42	51	82	200	395	610	805	1010	1350	1656	2775	3125	3790


DIN SERIES

Main size of outside & weight															900Lb
Size	in	2	2 1/2	3	4	6	8	10	12	14	16	18	20	24	
	mm	50	65	80	100	150	200	250	300	350	400	450	500	600	
L/L1 (RF/BW)	in	14.50	16.50	15.00	18.00	24.00	29.00	33.00	38.00	40.50	44.50	48.00	52.00	61.00	
	mm	368	419	381	457	610	737	838	965	1029	1130	1219	1321	1549	
L2 (RTJ)	in	14.62	16.62	15.12	18.12	24.12	29.12	33.12	38.12	40.88	44.88	48.50	52.50	61.75	
	mm	371	422	384	460	613	740	841	968	1038	1140	1232	1334	1568	
H	in	8.62	9.25	10.25	15.38	25.75	30.25	31.75	38.00	38.50	45.00	47.00	53.50	56.00	
	mm	219	235	260	390	655	770	805	965	980	1145	1195	1360	1425	
W	in	20	20	20	24	24	24	24	32	32	32	32	32	32	
	mm	500	500	500	600	600	600	600	800	800	800	800	800	800	
WT (Kg)	RF/RTJ	31	43	68	98	171	345	650	940	1205	1565	2050	2535	3950	
	BW	23	31	51	61	102	240	480	735	965	1215	1625	1995	3335	

JIS SERIES

Main size of outside & weight												1500Lb
Size	in	2	2 1/2	3	4	6	8	10	12	14	16	
	mm	50	65	80	100	150	200	250	300	350	400	
L/L1 (RF/BW)	in	14.50	16.50	18.50	21.50	27.75	32.75	39.00	44.50	49.50	54.50	
	mm	368	419	470	546	705	832	991	1130	1257	1384	
L2 (RTJ)	in	14.62	16.62	18.62	21.62	28.00	33.12	39.38	45.12	50.25	55.38	
	mm	371	422	473	549	711	841	1000	1146	1276	1407	
H	in	11.25	12.00	13.25	20.00	33.50	39.38	41.12	49.38	50.00	58.50	
	mm	285	306	338	506	852	1000	1045	1255	1270	1485	
W	in	20	20	24	24	24	32	32	32	32	32	
	mm	500	500	600	600	600	800	800	800	800	800	
WT (Kg)	RF/RTJ	49	67	106	153	268	540	1020	1475	1885	2455	
	BW	33	44	73	87	145	345	685	1050	1385	1735	

API Forged Steel Trunnion ball valve



ASTM Material list of cast steel trunnion mounted ball valve

No	Part Name	Carbon Steel to ASTM		Stainless Steel to ASTM				
1	Body	ASTM A105N	A350 LF2	A182 F304	A182 F316	A182 F304L	A182 F316L	A182 F51
2	Bonnet	ASTM A105N	A350 LF2	A182 F304	A182 F3316	A182 F304L	A182 F316L	A182 F51
3	Ball	A351 CF8	A351 CF8	A351 CF8	A351 CF8M	A351 CF3	A351 CF3M	CD4MCU
4	Stem	A182 F6a	A182 F304	A182 F304	A182 F316	A182 F304L	A182 F316L	A182 F51
5	Gasket	SS304 +Graphite, PDPE						
6	Seat	A105N+ENP	LF2+ENP	A182 F304	A182 F316	A182 F304L	A182 F316L	A182 F51
7	Clamping ring	A105N+ENP	LF2+ENP	A182 F304	A182 F316	A182 F304L	A182 F316L	A182 F51
8	Seat ring	PTFE, RTFE, PEEK, DELRIN						
9	Seat back	A105N+ENP	LF2+ENP	A182 F304	A182 F316	A182 F304L	A182 F316L	A182 F51
10	O-ring	Fluororubber						
11	Seat gasket	Flexible Graphite						
12	Stuffing box	A105N+ENP	LF2+ENP	A182 F304	A182 F316	A182 F304L	A182 F316L	A182 F51
13	Bolt	A193 B7/B7M	A320 L7/L7M	A193 B8/B8M				
14	Nut	A194 2H/2HM	A194 4/4M	A194 8/8M				
15	Spring	INCONEL X-750						
16	Screw	A193 B7	A320 L7	A193 B8/B8M				
17	Gasket	PTFE						
18	Flat key	Carbon Steel						
19	Shaft sleeve	PTFE						
20	Stem packing	PTFE Flexible Graphite						
21	Thrust washer	PTFE						
22	Packing gland	ASTM A105N	A350 LF2	A182 F304	A182 F316	A182 F304L	A182 F316L	A182 F51
23	Shaft sleeve	PTFE						
24	Support plate	ASTM A105N	A350 LF2	A182 F304	A182 F316	A182 F304L	A182 F316L	A182 F51
25	Yoke	Carbon Steel						
26	Pin	Carbon Steel						
27	Small check valve	ASTM A105N	A350 LF2	A182 F304	A182 F316	A182 F304L	A182 F316L	A182 F51
28	Grease injector	Carbon steel	Carbon steel	A182 F304	A182 F316	A182 F304L	A182 F316L	A182 F51
29	Vent plug	Carbon steel	Carbon steel	A182 F304	A182 F316	A182 F304L	A182 F316L	A182 F51
30	Drain plug	Carbon steel	Carbon steel	A182 F304	A182 F316	A182 F304L	A182 F316L	A182 F51
31	Lifting lug	Carbon Steel						
32	Support feet	Carbon Steel						


※

API SERIES

DIN SERIES

JIS SERIES

API Forged Steel Trunnion ball valve



API SERIES

DIN SERIES

JIS SERIES

Main size of outside & weight

150Lb

Size	in	2	2 1/2	3	4	6	8	10	12	14	16	18	20	24	26	28	30	32	36
	mm	50	65	80	100	150	200	250	300	350	400	450	500	600	650	700	750	800	900
L (RF)	in	7.00	7.50	8.00	9.00	15.50	18.00	21.00	24.00	27.00	30.00	34.00	36.00	42.00	45.00	49.00	51.00	54.00	60.00
	mm	178	190	203	229	394	457	533	610	686	762	864	914	1067	1143	1245	1295	1372	1524
L1 (BW)	in	8.50	9.50	11.12	12.00	18.00	20.50	22.00	25.00	30.00	33.00	36.00	39.00	45.00	49.00	53.00	55.00	60.00	68.00
	mm	216	241	283	305	457	521	559	635	762	838	914	991	1143	1245	1346	1397	1524	1727
H	in	4.00	6.00	7.00	9.25	9.88	11.00	12.62	15.38	16.50	21.88	23.62	25.00	28.00	29.50	31.50	34.00	36.00	38.50
	mm	120	150	180	235	250	280	320	390	420	555	600	635	710	750	800	865	915	980
W	in	16	16	24	24	24	24	32	32	32	32	32	32	32	40	40	40	40	40
	mm	400	400	600	600	600	600	800	800	800	800	800	800	800	1000	1000	1000	1000	1000
WT (Kg)	RF/RTJ	28	35	55	80	190	290	445	570	780	1520	2300	2500	3950	4890	6300	7100	8950	13500
	BW	25	28	49	71	182	277	423	553	747	1481	2266	2460	3904	4939	6362	8149	9000	13570

Main size of outside & weight

300Lb

Size	in	2	2 1/2	3	4	6	8	10	12	14	16	18	20	24	26	28	30	32	36
	mm	50	65	80	100	150	200	250	300	350	400	450	500	600	650	700	750	800	900
L (RF)	in	8.50	9.50	11.12	12.00	15.88	19.75	22.38	25.50	30.00	33.00	36.00	39.00	45.00	49.00	53.00	55.00	60.00	-
	mm	216	241	283	305	403	502	568	648	762	838	914	991	1143	1245	1346	1397	1524	-
L1 (BW)	in	8.50	9.50	11.12	12.00	18.00	20.50	22.00	25.00	30.00	33.00	36.00	39.00	45.00	49.00	53.00	55.00	60.00	-
	mm	216	241	283	305	403	521	559	635	762	838	914	991	1143	1245	1346	1397	1524	-
H	in	4.00	6.00	7.00	9.25	9.88	11.00	12.62	15.38	16.50	21.88	23.62	25.00	28.00	29.50	31.50	34.00	36.00	-
	mm	120	150	180	235	250	280	320	390	420	555	600	635	710	750	800	865	915	-
W	in	16	16	24	24	24	24	32	32	32	32	32	32	32	40	40	40	40	-
	mm	400	400	600	600	600	600	800	800	800	800	800	800	800	1000	1000	1000	1000	-
WT (Kg)	RF/RTJ	30	40	60	90	200	325	490	690	990	1810	2620	2860	4430	5430	6810	7655	9590	-
	BW	24	31	49	72	169	280	424	598	872	1665	2440	2635	4075	4880	6225	7115	9230	-

You are center of our world

API Forged Steel Trunnion ball valve



Main size of outside & weight															600Lb	
Size	in	2	2½	3	4	6	8	10	12	14	16	18	20	24	26	28
	mm	50	65	80	100	150	200	250	300	350	400	450	500	600	650	700
L/L1 (RF/BW)	in	11.50	13.00	14.00	17.00	22.00	26.00	31.00	33.00	35.00	39.00	43.00	47.00	55.00	57.00	61.00
	mm	292	330	356	432	559	660	787	838	889	991	1092	1194	1397	1448	1549
L2 (RTJ)	in	11.62	13.12	14.12	17.12	22.12	26.12	31.12	33.12	35.12	39.12	43.12	47.25	55.38	57.50	61.50
	mm	295	333	359	435	562	664	791	841	892	994	1095	1200	1407	1461	1562
H	in	6.50	7.00	7.88	11.00	12.25	14.00	16.12	18.00	19.25	21.00	24.88	25.62	30.12	31.88	34.62
	mm	165	180	200	280	310	355	410	455	490	535	630	650	765	810	880
W	in	16	24	24	24	32	32	32	32	32	32	40	40	40	40	40
	mm	400	600	600	600	800	800	800	800	800	800	1000	1000	1000	1000	1000
WT (Kg)	RF/RTJ	34	53	65	125	245	505	640	910	1380	2250	3400	3850	4900	6700	8300
	BW	27	43	49	95	188	418	495	740	1185	1960	3050	3406	4275	6025	7590

Main size of outside & weight														900Lb
Size	in	2	2 1/2	3	4	6	8	10	12	14	16	18	20	24
	mm	50	65	80	100	150	200	250	300	350	400	450	500	600
L/L1 (RF/BW)	in	14.50	16.50	15.00	18.00	24.00	29.00	33.00	38.00	40.50	44.50	48.00	52.00	61.00
	mm	368	419	381	457	610	737	838	965	1029	1130	1219	1321	1549
L2 (RTJ)	in	14.62	16.62	15.12	18.12	24.12	29.12	33.12	38.12	40.88	44.88	48.50	52.50	61.75
	mm	371	422	384	460	613	740	841	968	1038	1140	1232	1334	1568
H	in	6.72	7.50	8.25	11.38	12.62	15.38	17.00	18.50	20.88	24.00	26.00	27.50	30.75
	mm	170	190	210	290	320	390	430	470	530	610	660	700	780
W	in	24	24	24	32	32	32	32	32	32	40	40	40	40
	mm	600	600	600	800	800	800	800	800	800	1000	1000	1000	1000
WT (Kg)	RF/RTJ	45	65	73	135	360	650	930	1350	1890	3100	4300	4950	7100
	BW	37	53	56	98	291	545	760	1145	1650	2750	3875	4410	6485

Main size of outside & weight												1500Lb
Size	in	2	2 1/2	3	4	6	8	10	12	14	16	
	mm	50	65	80	100	150	200	250	300	350	400	
L/L1 (RF/BW)	in	14.50	16.50	18.50	21.50	27.75	32.75	39.00	44.50	49.50	54.50	
	mm	368	419	470	546	705	832	991	1130	1257	1384	
L2 (RTJ)	in	14.62	16.62	18.62	21.62	28.00	33.12	39.38	45.12	50.25	55.38	
	mm	371	422	473	549	711	841	1000	1146	1276	1407	
H	in	6.75	7.50	8.25	11.38	13.00	15.75	17.38	22.00	25.25	27.12	
	mm	170	190	210	290	330	400	440	560	640	690	
W	in	24	24	32	32	32	32	32	40	40	40	
	mm	600	600	800	800	800	800	800	1000	1000	1000	
WT (Kg)	RF/RTJ	55	75	95	150	540	880	1360	1980	3100	4650	
	BW	40	55	65	115	420	865	1025	1555	2600	3930	

API SERIES

DIN SERIES

JIS SERIES

Our butterfly valves are structured to centered seal, single eccentric seal, double eccentric seal, triple eccentric seal and variable eccentric seal. The sealing principles of these structures are stated as following.


Butterfly Valve



Sealing Principle of Double Eccentric Seal Butterfly Valve

The rotation center of disc (namely the center of valve shaft) and the centerline of body form up a 'b' eccentric on the base of single eccentric butterfly valve. Making the sealing face of disc disengaged from seat sealing face more quickly than single eccentric seal butterfly valves during the process of open and close. Once disc turns to $8^{\circ} \sim 12^{\circ}$, the disc sealing face will be completely disengaged from the seat sealing face. Once fully opened, a gap 'Y' will be formed up between the two sealing faces. This type of butterfly valves are designed to have greatly lowered the mechanical wear and extrusion deformation between the two sealing faces, making the sealing performance of butterfly valve much better.

The character rustic of this structure is to make stem axis not only deviated from the center of disc, but also the center of the body. The effect of double eccentric is that, when valve has been opened, disc can be quickly disengaged from seat, thus to greatly eliminate the unnecessary excessive extrusion and scratch between the disc and seat, reduce opening resistance, lower the abrasion and improve the service life of seat. As scratch has been greatly Lowered, metal seat can be used for double eccentric butterfly valve, so that butterfly valves are able to be used in high temperature fields. However, as its seal is positioned sealing construction, i.e. the sealing faces disc and seat is lineal contact, disc extruding seat to produce elastic deformation, thus to effect the sealing perforce has high requirement on close position, especially for lhasa with metal seat and is given poor pressure endurance. This is why butterfly valves are conventional IV, not resistant to high temperature and leakage.




Sealing Structure of Double Eccentric Seal Butterfly Valve

Sealing Principle of Triple Eccentric Seal Butterfly Valve

A B eccentric is formed up between the centerline of seat and the centerline of body on the base of double eccentric butterfly valve, making disc sealing face immediately disengaged from seat sealing face upon the opening of butterfly valve, and in close contact with the seat sealing face upon closing. When fully opened, a gap 'Y', which is the same as that in double eccentric seal butterfly valve, is formed up between the two sealing faces. The design of this type of valves has thoroughly eliminated the mechanical wear and scratch between the two sealing faces, making the sealing performance and service life of butterfly valves greatly improved. When valve is closed, with sealing ring under the extrusion of body sealing face and disc, two upward elastic deformations are produced. the sealing face is fallen under outward tension at long shaft and

inward compressive stress at short shaft. The long and short shafts produce elastic deformation of different directions, thus to maximizing the sealing force between the sealing faces of valve.

This distinctive eccentric combination not only uses cam effect, but also eliminates friction completely, thus to ensure no friction between seat and sealing ring on disc during the 90 ° stroke of valve, a perfect solution to clear away the possibilities of abrasion and leakage.




Close State Diagram of Triple Eccentric Seal Butterfly Valve

Open State Diagram of Triple Eccentric Seal Butterfly Valve

Sealing Principle of Triple Eccentric Seal Butterfly Valve


Butterfly valves are used to open and close (seal type) or adjust the medium flow in pipes in the fields of foodstuff, drinks, chemical, industrial water treatment, high-rise constructions, water supply and drainage etc. They are mainly structured as following:

1. Simple structure, small sizes, light weight and low installation dimensions. According to the types of body connection, they are basically classified to wafer type (including lug wafer type), flanged and welded.




1. Multilayer Hard Seal Structure (See fig. right)

Multilayer hard seal structure is applicable. double and triple eccentric butterfly valves, pressure rating $\leq$ CLASS 600. And triple eccentric butterfly valve can maintain two-way leak-tightness. Multilayer sealing ring is composite of stainless steel and nonmetal material. The nonmetal material can be flexible graphite, PTFE or non asbestos material etc. according to the actual working conditions.




Multilayer Hard Seal Structure

2. Elastic ring hard seal structure (see fig right) is of the structure of J-type metal sealing ring. It is applicable and double eccentric butterfly valves. pressure rating $\leq$ CLASS 300. Provided with fireproof structure to adapt to conditions with great temperature changes, it is featured by outstanding seal, long service life and easy workmanship.



Elastic Ring Hard Seal Structure


- When butterfly valve is fully opened, flow resistance is low. When partially opened, it may carry out sensitive flow control.
- Low driving moment, easy and quick operation.



API Butterfly Valve




The Triple Offset Geometry



ASTM Materials list of Butterfly Valve

No.	Part Name	Carbon Steel to ASTM	Stainless Steel to ASTM	
1	Body	A216 WCB	A351 CF8	A351 CF8M
2	Key	A182 F6a	SS304	SS316
2a	Pin		SS304	SS316
3	Stem		A182 F304	A182F316
4	Disc	A216 WCB	A351 CF8	A351 CF8M
5	Seal Ring	Graphite+304		
6	Retainer Flange	A216 WCB		
7	Bolt	A193 B7		
8	Bolt			
9	Cover			
10	Gasket	PTFE+Bronze		
11	Bushing	PTFE+Bronze		
12	Bushing	SS		
13	Packing Seat	Graphite		
14	Packing	-		
15	Bolt	SS		
16	Packing Bushing	-		
17	Nut	-		
18	Bolt	-		
19	Yoke	Carbon Steel		


API Triple Offset Butterfly Valve



API 150LB Wafer , LUG, Flange Butterfly

Nominal Diameter		Structure Length						External Dimension				Connection Dimension								Weight kg	
		Wafer L		LUG L1		Flange L2		H		H0		D		D1		D2		Z- d			
inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm			Wafer	Flange
2"	50	1.69	43	1.69	43	4.25	108	4.33	110	13.58	345	6	150	4.75	120.5	3.625	92	4-19	9	20	
3"	80	1.88	48	1.88	48	4.50	114	4.92	125	14.96	380	7	190	6	152.5	5.000	127	4-19	11	29	
4"	100	2.12	54	2.12	54	5.00	127	5.70	145	16.34	415	7.50	230	7.5	190.5	6.19	157	8-19	13	33	
5"	125	2.19	56	2.19	56	5.50	140	6.50	165	17.91	455	9	255	8.5	216	7.31	186	8-22	16	38	
6"	150	2.25	57	2.25	57	5.50	140	6.89	175	21.45	545	10	280	9.5	241.5	8.5	216	8-22	26	74	
8"	200	2.50	64	2.50	64	6.00	152	8.26	210	24.21	615	11	345	11.75	298.5	10.625	270	8-22	34	86	
10"	250	2.81	71	2.81	71	6.50	165	9.84	250	27.36	695	13.50	405	14.25	362	12.75	324	12-25	51	142	
12"	300	3.19	81	3.19	81	7.00	178	11.24	285	32.78	830	19	485	17	432	15	381	12-25	72	167	
14"	350	3.62	92	3.62	92	7.50	190	12.60	320	35.43	900	21	535	18.75	476	16.25	413	12-29	106	218	
16"	400	4.00	102	4.00	102	8.50	216	13.98	355	38.58	980	23.5	600	21.25	540	18.5	470	16-29	133	275	
18"	450	4.50	114	4.50	114	8.75	222	14.96	380	40.55	1030	25	635	22.25	578	21	533	16-32	176	315	
20"	500	5.00	127	5.00	127	9.00	229	16.34	415	43.70	1110	27.5	700	25.00	635	23	584	20-32	190	395	
24"	600	6.06	154	6.06	154	10.50	267	18.70	475	51.37	1305	32	815	29.5	749.5	27.25	692	20-35	394	580	
26"	650	6.50	165	6.50	165	11.50	292	20.85	530	54.72	1390	34.25	870	31.75	806.5	29.25	749	24-35	415	620	
28	700	6.50	165	6.50	165	11.50	292	22.04	560	58.07	1475	36.5	927	34.00	863.6	31.5	800	28-35	435	650	
30"	750	6.50	165	6.50	165	12.52	318	22.38	580	60.03	1525	38.75	984	36.00	914.4	33.75	857	28-35	476	717	
32"	800	7.50	190	7.50	190	12.50	318	24.80	630	62.40	1585	41.75	1060	38.5	978	36.00	914	28-41	618	880	
34	850	7.88	200	7.88	200	13.00	330	25.60	650	63.00	1600	43.75	1111	40.5	1029	38.00	965	32-41	670	980	
36"	900	7.88	200	7.88	200	13.00	330	26.77	680	69.48	1765	46.00	1168	42.75	1086	40.25	1022	32-41	762	1042	
38"	950	7.88	200	7.88	200	16.14	410	27.95	710	72.84	1850	48.75	1238	45.25	1149	42.25	1073	32-41	960	1250	
40"	1000	8.50	216	8.50	216	16.14	410	29.53	750	76.00	1930	50.75	1289	47.25	1200.2	44.25	1124	36-41	1050	1500	

API Triple Offset Butterfly Valve



API SERIES


DIN SERIES

JIS SERIES


API 300LB Wafer , LUG, Flange Butterfly

Nominal Diameter		Structure Length								External Dimension				Connection Dimension								Weight JkgJ	
		Wafer L		LUG L1		Flange (Short) L2		Flange (Long) L2		H		H0		D		D1		D2		Z-d			
		inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm		inch	mm	Wafer
2"	50	1.69	43	1.69	43	4.25	108	—	—	4.33	110	13.58	345	6.5	165	5.0	127	3.62	92	8–19	9	20	
3"	80	1.88	48	1.88	48	4.50	114	7.09	180	4.92	125	14.96	380	8.25	210	6.62	168.5	5.0	127	8–22	12	29	
4"	100	2.12	54	2.12	54	5.00	127	7.48	190	5.70	145	16.34	415	10	25	7.88	200	6.19	157	8–22	13	35	
5"	125	2.19	56	2.19	56	5.50	140	—	—	6.50	165	17.91	455	11	280	9.25	235	7.31	186	8–22	18	40	
6"	150	2.31	59	2.31	59	5.50	140	8.27	210	6.89	175	21.45	545	12.5	320	10.62	270	8.5	216	12–22	28	81	
8"	200	2.88	73	2.88	73	6.00	152	9.06	230	8.26	210	24.21	645	15	380	13.0	330	10.62	270	12–26	37	94	
10"	250	3.25	83	3.25	83	6.50	165	9.84	250	9.84	250	27.36	695	17.5	445	15.25	387.5	12.75	324	16–29	56	158	
12"	300	3.62	92	3.62	92	7.00	178	10.63	270	11.24	285	32.78	830	20.5	520	17.75	451	15.0	381	16–32	79	183	
14"	350	4.62	117	4.62	117	7.50	190	11.42	290	12.60	320	35.43	900	23.0	585	20.25	514.5	16.25	413	20–32	116	239	
16"	400	5.25	133	5.25	133	8.50	216	12.20	310	13.98	355	38.58	980	25.5	650	22.5	571.5	18.5	470	20–35	146	302	
18"	450	5.88	149	5.88	149	8.74	222	12.99	330	14.96	380	40.55	1030	28.0	710	24.75	628.5	21.0	533	24–35	193	346	
20"	500	6.25	159	6.25	159	9.00	229	13.78	350	16.34	415	43.70	1110	30.5	775	27.0	686	23.0	584	24–35	209	434	
24"	600	7.12	181	7.12	181	10.50	267	15.35	390	18.70	475	51.37	1305	36.0	915	32.0	813	27.25	692	24–41	433	638	
26"	650	8.25	210	8.25	210	11.50	292	16.14	410	20.00	510	54.0	1370	38.25	972	34.5	876.3	29.5	749	28–45	450	650	
28"	700	9.01	229	9.01	229	11.50	292	16.93	430	22.04	560	58.07	1475	40.75	1035	37.0	934	31.5	800	28–45	498	698	
30"	750	9.01	229	9.01	229	12.52	318	17.72	450	22.38	580	60.03	1525	43.0	1092	39.25	997	33.75	857	28–48	523	788	
32"	800	9.48	241	9.48	241	12.52	318	18.50	470	25.59	650	64.37	1635	45.25	1149	41.5	1054.1	36.0	914	28–51	588	988	
34"	850	9.50	241	9.50	241	13.00	330	20.80	510	26.00	660	66.0	1675	47.5	1207	43.5	1105	38.0	965	32–51	750	1050	
36"	900	9.48	241	9.48	241	13.00	330	20.80	510	26.77	680	69.48	1765	50.0	1270	46.0	1168.4	40.25	1022	32–54	838	1146	
38"	950	11.80	300	11.80	300	16.15	410	20.87	530	28.5	725	72.0	1830	46.0	1168	43.0	1092.2	40.5	1029	32–41	1200	1450	
40"	1000	11.80	300	11.80	300	16.15	410	21.65	550	31.0	785	78.0	1980	48.75	1238	45.5	1156	42.75	1086	32–45	1600	2000	

API Triple Offset Butterfly Valve



Flange Butterfly



API 600LB Flange Butterfly

API 600LB Flange Butterfly															
Nominal Diameter		Face-to-face (Standard)		External Dimension				Connection Dimension							Reference Weight [kg]
		L		H		H0		D		D1		D2		Z-d	
inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm		
2	50	5.90	150	4.5	115	15.0	380	6.5	165	5.0	127	3.62	92	8-19	20
3	80	7.10	180	6.1	155	17.5	445	8.25	210	6.62	168.3	5.0	127	8-22	35
4	100	7.48	190	7.8	195	20.8	530	10.72	275	8.5	215.9	6.19	157	8-26	60
5	125	7.88	200	8.8	225	23.2	590	13.0	330	10.5	266.7	7.31	186	8-29	90
6	150	8.25	210	9.4	240	24.5	620	14.0	355	11.5	292.1	8.5	216	12-29	120
8	200	9.05	230	11.0	280	29.0	735	16.5	420	13.75	349.2	1.62	270	12-32	170
10	250	9.85	250	12.4	315	32.0	810	20.0	510	17.0	431.8	12.75	324	16-35	250
12	300	10.62	270	13.5	345	34.5	875	22.0	560	19.25	489	15.0	381	20-35	340
14	350	11.42	290	14.5	370	37.8	960	23.75	605	20.75	527	16.25	413	20-39	450
16	400	12.20	310	16.5	420	41.7	1060	27.0	685	23.75	603.2	18.5	470	20-42	570
18	450	13.00	330	17.5	445	43.7	1110	29.25	745	25.75	654	21.0	533	20-45	700
20	500	13.78	350	19.0	485	50.0	1270	32.0	815	28.5	723.9	23.0	584	24-45	900
24	600	15.36	390	22.5	570	56.7	1440	37.0	940	33.0	838.2	27.25	692	24-51	1300
26	650	16.15	410	23.0	585	60.0	1525	40.0	1016	36.0	914.4	29.56	749	28-51	1600
28	700	16.93	430	24.5	620	62.6	1590	42.25	1073	38.0	965.2	31.5	800	28-55	1800
30	750	17.72	450	25.5	650	65.0	1650	44.5	1130	40.25	1022.4	33.75	857	28-55	2000
32	800	18.50	470	27.0	685	68.9	1750	47.0	1194	42.5	1079.5	36.0	914	28-60	2300
34	850	19.30	490	28.0	710	71.0	1800	49.0	1245	44.5	1130.3	38.0	965	28-60	2500
36	900	20.08	510	30.5	775	76.0	1930	51.75	1314	47.0	1194	40.25	1022	28-67	2800
38	950	20.86	530	29.8	755	75.2	1910	50.0	1270	45.75	1162	41.5	1054	28-60	2700
40	1000	21.65	550	31.5	800	78.7	2000	52.0	1321	47.75	1213	43.75	1111	32-60	3000

API SERIES

DIN SERIES

JIS SERIES

API Forged Steel Gate Valves




API SERIES

DIN SERIES

JIS SERIES

Forged Steel Gate Valves




◎ Forged steel gate valves

Our company are available in three bonnet designs. The first design is the Bolted Bonnet, with male-female joint, spiral wound gasket, made in F304L/graphite, Ring joint gasket are also available on request. The second design is the welded bonnet, with a threaded and seal welded joint. On request a full penetration strength welded joint is available. The third design is the pressure seal bonnet, with a threaded and pressure seal bonnet joint.


◎ Construction is as follows

- ※ Full port or conventional port;
- ※ Outside screw and yoke (OS & Y);
- ※ Two piece self-aligning packing gland;
- ※ Bolted bonnet & spiral wound gasket seal bonnet;
- ※ Bolted bonnet with spiral-wound gasket, threaded and seal welded bonnet or threaded and pressure seal bonnet;
- ※ Integral backseat;
- ※ Socket weld ends to ASME B16.11;
- ※ Screwed ends (NPT) to ANSI/ASME B1.20.1.



Application standards

- 1' Design and manufacture conform to
API 602' BS5352' ANSI B16.34;
- 2' Connection ends conform to''
1)Socket welded dimension conform to ANSI B16.11
2)Screw ends dimension conform to ANSI B1.20.1
3)Butt-welded conform to ANSI B16.25
4)Flanged ends conform to ANSI B16.5
- 3' Test and inspection conform to:
API 598
- 4' Structure features''
Bolted bonnet, outside screw and yoke;
Welded bonnet, outside screw and yoke.
- 5' Materials conform to ANIS/ASTM.
- 6' Main materials''
A105'' LF2'' F5'' F11'' F22'' F304'' F304L'' F316''
F316L'' F321'' F51'' F53'' Monel'' Alloy Steel.



Main part materials list

NO.	Part name	A105/F6a	A105/F6aHFS	LF2/304	F11/F6aHF	F304(L)/304(L)	F316(L)/316(L)	F51/F51
1	Body	A105	A105	LF2	F11	F304(L)	F316(L)	F51
2	Seat	410	410HF	304	410HF	304(L)	316(L)	F51
3	Wedge	F6a	F6a	F304	F6aHF	F304(L)	F316(L)	F51
4	Stem	410	410	304	410	304(L)	316(L)	F51
5	Gasket	304+graphite	304+graphite	304+graphite	304+graphite	304+graphite	316+graphite	316+graphite
6	Bonnet	A105	A105	LF2	F11	F304(L)	F316(L)	F51
7	Bolt	B7	B7	L7	B16	B8(M)	B8(M)	B8M
8	Pin	410	410	410	410	304	304	304
9	Gland	410	410	304	410	304	316	F51
10	Gland eyebolt	B7	B7	L7	B16	B8(M)	B8(M)	B8M
11	Gland flange	A105	A105	LF2	F11	F304	F304	F304
12	Hex nut	2H	2H	2H	2H	8(M)	8(M)	8M
13	Stem nut	410	410	410	410	410	410	410
14	Locking nut	35	35	35	35	35	35	35
15	Nameplate	AL	AL	AL	AL	AL	AL	AL
16	Handwheel	A197	A197	A197	A197	A197	A197	A197
17	Lubricating gasket	410	410	410	410	410	410	410
18	Packing	Graphite	Graphite	Graphite	Graphite	Graphite	Graphite	Graphite





API Forged Steel THD and SW Gate Valve



API SERIES

DIN SERIES

JIS SERIES



CL800

Bolted bonnet, full port reduced port outside screw and yoke(OS & Y)
Threaded, butt-welded or socket welded ends; design to API 602

Specification	R.P	1/2	3/4	1	1 1/4	1 1/2	2	2 1/2	3
	F.P	3/8	1/2	3/4	1	1 1/4	1 1/2	2	2 1/2
Face to face	L	79	92	111	120	120	140	178	180
Handwheel diameter	W	100	100	125	160	160	180	200	220
Height	H	161	163	196	223	251	290	333	370
Flow port dimension	d	10.5	13.5	18	24	29	36.5	45	51
Weight(Kg)		2.22	2.39	4.24	5.7	7.05	10.9	16.8	24

CL900-CL1500

Bolted bonnet, full port reduced port outside screw and yoke(OS&Y)
Threaded, butt-welded or socket welded ends; design to API 602

Specification	R.P	1/2	3/4	1	1 1/4	1 1/2	2	2 1/2
	F.P	3/8	1/2	3/4	1	1 1/4	1 1/2	2
Face to face	L	111	111	120	120	140	178	180
Handwheel diameter	W	125	125	160	160	180	200	220
Height	H	191	192	219	243	296	316	370
Flow port dimension	d	10.5	13.5	18	24	29	36.5	45
Weight(Kg)		4.4	4.3	6	7.2	11.4	16	23

CL1500-CL2500

Welded bonnet, full port or red. port, outside screw and yoke(OS&Y)
Threaded, butt-welded or socket welded ends; design to API 602

Specification(NPS)	F.P	Pressure pound level	1/2	3/4	1	1 1/2	2
Face to face	L	CL1500	110	150	150	210	235
Handwheel diameter	W	CL1500	110	130	130	180	250
Height	H	CL1500	277	300	390	400	435
Flow port dimension	d	CL1500	14	17	22	35	37
Weight(Kg)		CL1500	5.1	11	12.1	22	37

CL1500-CL2500

Pressure seal bonnet, full port outside screw and yoke(OS & Y)
Socket welded ends, design conform to ASME B16.34

Specification	F.P	Pressure pound level	1/2	3/4	1	1 1/4	1 1/2	2
Face to face	L	CL2500	186	186	186	232	232	279
Handwheel diameter	W	CL2500	200	200	200	280	280	300
Height	H	CL2500	325	325	327	467	468	540
Flow port dimension	d	CL2500	14	14	19	25	30	36.5
Weight(Kg)		CL2500	12.3	11.6	10.8	26.0	28.4	60.0

You are center of our world


API Forged Steel Flange Gate Valve



API SERIES

DIN SERIES

JIS SERIES



CL150-300-600

Bolted bonnet, red., outside screw and yoke(OS & Y)

Flange-welded or butt-welded ends; design to API602;BS5352

Specification			1/2	3/4	1	1 1/4	1 1/2	2	2 1/2
Face to face (mm)	CL150	L(RF)	108	117	127	140	165	178	190
	CL300	L1(BW)	140	152	165	178	190	216	241
	CL600		165	190	216	229	241	292	330
Handwheel diameter		W	100	100	125	160	160	180	200
Height	CL150	H	176	184	217	226	250	290	357
	CL300,CL600		161	163	196	226	250	290	357
Flow port dimension		d	10	13.5	18	24	29	36.5	45
Weight (Kg)	CL150	RF	3.4	3.98	6.12	7.2	10.4	15.5	24.5
		BW	2.8	3.3	5.4	7.1	8.2	12.5	20
	CL300	RF	3.77	4.89	7.23	9.6	12.65	18	26.2
		BW	3.5	4.4	6.8	8.1	9.2	15.4	22
	CL600	RF	4.2	5.8	8.8	12.1	15.6	19.5	32
		BW	4.5	5.1	8.2	10.5	12.4	20.1	28

CL900-CL1500

Bolted bonnet, red., outside screw and yoke(OS & Y)

Flange-welded or butt-welded ends; design to API602;BS5352

Specification			1/2	3/4	1	1 1/4	1 1/2	2
Face to face (mm)	L(RF) L1(BW)		216	229	254	279	305	368
	L(RTJ)		216	229	254	279	305	371
Handwheel diameter	W		125	125	160	180	200	220
Height	H		191	192	219	257	296	316
Flow port dimension	d		13.5	18	24	29	36.5	45
Weight (Kg)			7.2	11.5	15.6	16.2	22.6	28.2

CL2500

Welded bonnet, red., outside screw and yoke(OS & Y)

Flange-welded or butt-welded ends; design to API602;BS5352

Specification			1/2	3/4	1	1 1/2	2
Face to face (mm)	L(RF) L1(BW)		264	273	308	384	451
	L(RTJ)		264	273	308	387	454
Handwheel diameter	W		125	160	160	200	240
Height	H		207	240	258	355	370
Flow port dimension	d		13.5	13.5	19	30	36.5
Weight (Kg)			19.5	21.5	42	65	95

CL2500

Pressure seal gate valves, red., outside screw and yoke(OS & Y)

Flange-welded or butt-welded ends; design to ASME B16.34

Specification			1/2	3/4	1	1 1/2	2
Face to face (mm)	L(RF) L1(BW)		264	273	308	384	451
	L(RTJ)		264	273	308	387	451
Handwheel diameter	W		200	200	200	280	300
Height	H		325	325	327	478	540
Flow port dimension	d		13.5	13.5	19	30	36.5
Weight (Kg)			4.6	6.8	7.6	15	21.9

API Forged Steel Globe Valves




API SERIES

DIN SERIES

JIS SERIES

Forged Steel Globe Valves




● Forged steel globe valves

Our company are available in three bonnet designs. The first design is the Bolted Bonnet, with male-Female joint, spiral wound gasket, made in F304L/graphite, Ring joint gasket are also available on request. The second design is the welded bonnet, with a threaded and seal welded joint. On request a full penetration strength welded joint is available. The third design is the pressure seal bonnet, with a threaded and pressure seal bonnet joint.

● Construction is as follows

- ※ Full port or conventional port;
- ※ Outside screw and yoke (OS&Y);
- ※ Two piece self-aligning packing gland;
- ※ Bolted bonnet with spiral-wound gasket, threaded and seal welded bonnet or threaded and pressure seal bonnet;
- ※ Integral backseat;
- ※ Socket weld ends to ASME B16.11;
- ※ Screwed ends(NPT) to ANSI/ASME B1.20.1;
- ※ Disc can change for throttle type、needle type、ball type and check type.




API Forged Steel Globe Valves



Application standards

- 1' Design and manufacture conform to BS5352 MSS SP-118
- 2' Connection ends conform to
 - 1)Socket welded ends conform to ANSI B16.11
 - 2)Screw ends conform to ANSI B1.20.1
 - 3)Butt-welded ends conform to ANSI B16.25
 - 4)Flanged ends conform to ANSI B16.5
- 3' Test and inspection conform to
 - API 598
- 4' Structure features
 - Bolted bonnet, outside screw and yoke;
 - Welded bonnet, outside screw and yoke.
- 5' Materials conform to ANSI/ASTM.
- 6' Main materials
 - A105 LF2 F5 F11 F22 F304 F304L F316
 - F316L F321 F51 F53 Monel Alloy Steel.



Main part materials list

NO.	Part name	A105/F6a	A105/F6aHFS	LF2/304	F11/F6aHF	F304(L)/304(L)	F316(L)/316(L)	F51/F51
1	Body	A105	A105+HF	LF2	F11+HF	F304(L)	F316(L)	F51
3	Disc	F6a	F6a	F304	F6aHF	F304(L)	F316(L)	F51
4	Stem	410	410	304	410	304(L)	316(L)	F51
5	Gasket	304+ graphite	304+ graphite	304+ graphite	304+ graphite	304+ graphite	316+ graphite	316+ graphite
6	Bonnet	A105	A105	LF2	F11	F304(L)	F316(L)	F51
7	Bolt	B7	B7	L7	B16	B8(M)	B8(M)	B8M
8	Pin	410	410	410	410	304	304	304
9	Gland	410	410	304	410	304	316	F51
10	Gland eyebolt	B7	B7	L7	B16	B8(M)	B8(M)	B8M
11	Gland flange	A105	A105	LF2	F11	F304	F304	F304
12	Hex nut	2H	2H	2H	2H	8(M)	8(M)	8M
13	Stem nut	410	410	410	410	410	410	410
14	Locking nut	35	35	35	35	35	35	35
15	Nameplate	AL	AL	AL	AL	AL	AL	AL
16	Handwheel	A197	A197	A197	A197	A197	A197	A197
18	Packing	Graphite	Graphite	Graphite	Graphite	Graphite	Graphite	Graphite

API SERIES

DIN SERIES

JIS SERIES


API Forged Steel THD and SW globe valves



API SERIES

DIN SERIES


JIS SERIES



CL800

Bolted bonnet, full port or red. port outside screw and yoke(OS & Y)
THD., SW or BW ends, design standard: BS5352


Specification	R.P	1/2	3/4	1	1 1/4	1 1/2	2	2 1/2
	F.P	3/8	1/2	3/4	1	1 1/4	1 1/2	2
Face to face	L	79	92	111	120	152	172	200
Handwheel diameter	W	100	100	125	160	160	180	200
Height	H	164	164	203	224	260	300	355
Flow port dimension	d	9	13	17.5	23	30	35	46
Weight(Kg)		2.28	2.37	4.3	5.75	7.8	12.5	17.5



CL900-CL1500

Bolted bonnet, red. port or full port outside screw and yoke(OS&Y)
THD.,BW or SW ends, design standard: BS5352


Specification	R.P	1/2	3/4	1	1 1/4	1 1/2	2	2 1/2
	F.P	3/8	1/2	3/4	1	1 1/4	1 1/2	2
Face to face	L	111	111	120	152	172	200	220
Handwheel diameter	W	125	125	160	160	180	200	240
Height	H	207	207	240	258	330	355	370
Flow port dimension	d	12	15	20	28	32	40	45
Weight(Kg)		3.7	3.6	6.8	7.6	11.6	15	21.9



CL2500

Welded bonnet (RJ), red. port, outside screw and yoke(OS & Y)
SW ends, design standard: ASME B16.34

Specification	F.P	1/2	3/4	1	1 1/2	2
Face to face	L	150	150	210	235	235
Handwheel diameter	W	130	130	250	300	300
Height	H	293	300	390	435	435
Flow port dimension	d	11	14	19	28	35
Weight(Kg)		10	10.3	22.4	38	38



CL2500

Pressure seal bonnet, red. port, outside screw and yoke(OS & Y)
SW ends, design standard:ASME B16.34

Specification	F.P	1/2	3/4	1	1 1/4	1 1/2	2
Face to face	L	186	186	186	232	232	279
Handwheel diameter	W	200	200	200	280	280	300
Height	H	375	378	380	490	490	540
Flow port dimension	d	11	14	19	25	28	35
Weight(Kg)		12.3	11.6	10.8	26.0	28.4	60

You are center of our world





API Forged Steel Flange Globe Valve



API SERIES

DIN SERIES

JIS SERIES



CL150-300-600

Bolted bonnet, reducing port, outside screw and yoke(OS & Y)
Flanged or BW ends, design standard: BS5352

Specification			R.P	1/2	3/4	1	1 ¹ /4	1 ¹ /2	2
Face to face	CL150	L(RF) L1(BW)	108	117	127	140	165	203	
	CL300		152	178	203	216	229	267	
	CL600		165	190	216	229	241	292	
Handwheel diameter		W	100	100	125	160	160	180	
Height	CL150/CL300	H	180	184	217	224	260	300	
	CL600		164	164	203	224	260	300	
Flow port dimension(mm)			d	9	13	17.5	23	30	35
Weight (Kg)	CL150	R F	3.45	4.00	6.19	9.6	10.5	17	
		BW	2.3	3.6	7.8	8.2	12.0	15.0	
	CL300	R F	3.8	5.1	7.2	12	13.5	19.7	
		BW	2.8	4.0	8.5	9.2	12.6	16.8	
	CL600	R F	5.6	7.8	12.5	17	23.5	38.8	
		BW	3.4	4.7	9.2	10.5	13.3	18.9	

CL900-CL1500

Bolted bonnet, reducing port, outside screw and yoke(OS & Y)
Flanged or BW ends, design standard: BS5352

Specification	F.P	1/2	3/4	1	1 ¹ /4	1 ¹ /2	2
Face to face (mm)	L(RF), L1(BW)	216	229	254	279	305	368
	L(RTJ)	216	229	254	279	305	371
Handwheel diameter(mm)	W	125	125	160	160	180	200
Height(mm)	H	207	207	230	160	300	355
Flow port dimension(mm)	d	12	15	20	28	32	40
Weight (Kg)		11	13.2	17.4	19	24.5	31

CL2500

Welded bonnet, reducing port, outside screw and yoke(OS & Y)
Flanged or BW ends, design standard: ASME B16.34

Specification	F.P	1/2	3/4	1	1½	2
Face to face (mm)	L(RF), L1(BW)	264	273	308	384	451
	L(RTJ)	264	273	308	387	454
Handwheel diameter(mm)	W	125	160	200	250	240
Height(mm)	H	207	240	258	355	300
Flow port dimension(mm)	d	11	14	19	28	35
Weight (Kg)		19.5	21.5	42	65	95

CL2500

Pressure seal bonnet, reducing port, outside screw and yoke(OS & Y)
Flanged or BW ends, design standard: ASME B16.34

Specification	F.P	1/2	3/4	1	1 1/4	1 1/2	2
Face to face (mm)	L(RF), L1(BW)	264	273	308	349	384	451
	L(RTJ)	264	273	308	349	387	454
Handwheel diameter(mm)	W	200	200	280	280	280	300
Height(mm)	H	320	320	320	440	440	490
Flow port dimension(mm)	d	11	14	19	25	28	35
Weight (Kg)		21.5	24.7	30.4	48.1	58.1	130

API Forged Steel Check Valves




API SERIES

DIN SERIES

JIS SERIES

Forged Steel Check Valves




● Forged steel check valves

Our company are available in three bonnet designs. The first design is the Bolted Bonnet, with male-female joint, spiral wound gasket, made in F304L/graphite, Ring joint gasket are also available on request. The second design is the welded bonnet, with a threaded and seal welded joint. On request a full penetration strength welded joint is available. The third design is the pressure seal bonnet, with a threaded and pressure seal bonnet joint. The check valves are also available in three different design configurations. These are piston check, ball check, or swing check designs.

● Construction is as follows

- ※ Full port or conventional port;
- ※ Lift type check valves;
- ※ Ball type check valves;
- ※ Swing type check valves;
- ※ According to requirement equip inside spring;
- ※ Bolted bonnet with spiral-wound gasket, threaded and seal welded bonnet or threaded and pressure seal bonnet;
- ※ Socket weld ends to ASME B16.11;
- ※ Screwed ends (NPT) to ANSI/ASME B1.20.1;
- ※ Disc can change for soft seal disc and ball disc.




API Forged Steel Check Valves



Application standards

- 1、 Design and manufacture conform to BS5352 MSS SP-118;
- 2、 Connection ends conform to:
 - 1)Socket welded ends conform to ANSI B16.11
 - 2)Screw ends conform to ANSI B1.20.1
 - 3)Butt-welded ends conform to ANSI B16.25
 - 4)Flanged ends conform to ANSI B16.5
- 3、 Test and inspection conform to: API 598
- 4、 Structure features:
 - Bolted bonnet
- 5、 Materials conform to ANSI/ASTM.
- 6、 Main materials:
 - A105; LF2; F5; F11; F22; F304;
 - F304L; F316; F316L; F321; F51;
 - F53; Monel; Alloy Steel.



Main part materials list

NO.	Part name	A105/F6a	A105/F6aHFS	LF2/304	F11/F6aHF	F304(L)/304(L)	F316(L)/316(L)	F51/F51
1	Body	A105	A105	LF2	F11	F304(L)	F316	F51
2	Seat ring	410	410HF	304	410HF	304(L)	316(L)	F51
3	Disc	F6a	F6a	F304	F6aHF	F304(L)	F316(L)	F51
5	Gasket	304+G	304+G	304+G	304+G	304+G	316+G	316+G
6	Bonnet	A105	A105	LF2	F11	F304(L)	F316(L)	F51
7	Bolt	B7	B7	L7	B16	B8(M)	B8(M)	B8M
15	Nameplate	AL	AL	AL	AL	AL	AL	AL
32	Revit	AL	AL	AL	AL	AL	AL	AL
33	Steel ball	430	430	304	STL	316(L)	316(L)	STL
34	Disc nut	2H	2H	8	8	8(M)	8(M)	8M
35	Hinge	410	410	304	410	316(L)	316(L)	F51
36	Pin	410	410	304	410	304(L)	316(L)	F51

API SERIES

DIN SERIES

JIS SERIES


API Forged Steel Check Valves




API SERIES

DIN SERIES



JIS SERIES



Spring-load acc. to client's requirement



Spring-load acc. to client's requirement



CL800

BB, Full Bore or Red. Bore, THD or BW or SW ends, Design Standard: BS5352

Specification	R.P	-	1/2	3/4	1	1 1/4	1 1/2	2	2 1/2
	F.P	-	3/8	1/2	3/4	1	1 1/4	1 1/2	2
Face to face	L	Lift	79	92	111	120	152	172	200
		Swing	79	92	111	120	120	140	178
Height	H	Lift	61	61	78	84	84	118	132
		Swing	61	61	78	84	84	120	133
Flow port dimension	d	Lift	9	13	17.5	23	30	35	46
		Swing	10.5	13.5	18	24	29	36.5	45
Weight(Kg)		Lift	1.5	1.7	3.3	4.2	4.2	10.5	12.5
		Swing	1.5	1.7	3.3	4.2	4.2	8.5	10.9

CL900-CL1500

Specification	R.P	-	1/2	3/4	1	1 1/4	1 1/2	2	2 1/2
	F.P	-	3/8	1/2	3/4	1	1 1/4	1 1/2	2
Face to face	L	Lift	92	111	111	120	152	172	200
		Swing	92	111	111	120	120	140	178
Height	H	Lift	61	78	78	84	103	118	132
		Swing	61	78	78	84	101	120	133
Flow port dimension	d	Lift	7	12	15	20	28	32	40
		Swing	8	10.5	13.5	18	24	29	45
Weight(Kg)		Lift	1.5	3.4	3.3	4.2	6.3	10.5	12.5
		Swing	1.5	3.4	3.3	4.2	5.0	8.5	10.9

CL150-300-600

Specification		R.P	1/2	3/4	1	1 1/4	1 1/2	2
Face to face	CL150	L(RF) L1(BW)	108	118	127	140	165	203
	CL300		153	178	203	216	229	267
	CL600		165	191	216	229	241	292
Height	CL150	H	77	81	93	95	103	118
	CL300/600		61	78	84	101	120	133
Flow port dimension(mm)		d	10	13	17.5	23	30	35
Weight (Kg)	CL150	RF	3.6	4.6	8.5	9.2	12.5	14.8
		BW	3.0	3.6	7.6	8.5	11.3	13.6
	CL300	RF	3.7	4.8	8.8	9.6	13.7	17.8
		BW	3.2	4.3	8.0	8.6	12.7	16.2
	CL600	RF	4.0	5.8	9.5	10.4	15.6	24.5
		BW	3.4	5.1	8.8	9.2	14.8	22.5

CL150-300-600

Specification		R.P	1/2	3/4	1	1 1/4	1 1/2	2
Face to face	CL150	L(RF) L1(BW)	108	118	127	140	165	203
	CL300		153	178	203	216	229	267
	CL600		165	191	216	229	241	292
Height	CL150	H	77	81	93	95	103	118
	CL300/600		61	78	84	101	120	133
Flow port dimension(mm)		d	10.5	13.5	18	24	29	36.5
Weight (Kg)	CL150	RF	3.6	4.6	8.5	9.2	12.5	14.8
		BW	3.0	3.6	7.6	8.5	11.3	13.6
	CL300	RF	3.7	4.8	8.8	9.6	13.7	17.8
		BW	3.2	4.3	8.0	8.6	12.7	16.2
	CL600	RF	4.0	5.8	9.5	10.4	15.6	24.5
		BW	3.4	5.1	8.8	9.2	14.8	22.5

You are center of our world

DIN Gate Valve



Product structural features

Gate valve seal acc. to DIN is applicable to the cutting and connection of pipelines medium that are used in various industries such as petroleum, chemical industry, pharmacy, chemical fertilizer, electric power industry, etc under nominal pressure of PN1.6~16MPa and working temperature within industries -110~600℃

Main structural features

1. This product has logical structure, reliable seal, excellent performance and nice design.
2. The seal surface is build-up welding with Wc-Co hard alloy, which is attrition-resistant, corrosion-resistant, has good friction resistant and long life.
3. The stem quenched and tempered, and its surface is treated by nitrating treatment, thus it has good corrosion resistant and friction resistant.
4. It has double seal capability, which is more reliable.
5. The part material, flange and butt weld end dimension may be selected according to current operating condition and users' requirement, so that meeting the requirements of various engineering.

Technical specification

Structural Formation: BB-BG-OS & Y
Driving Manner: Hand-Operated
Driving Manner: Electric-Actuated
Design Standard: DIN3352
Face to Face: DIN3202
Flange Ends: DIN2543-2547
Test & Inspection: DIN3230

Notes: The size of serial, valve connecting flange can be design according to customers' requirement.


Product Performance Specification

Nominal Pressure (MPa)	Shell Test (MPa)	Sealing Test (MPa)	Suitable Temp (°C)	Suitable Medium
1.6	2.4	1.76	-110~600℃	Water Oil & Gas
2.5	3.75	2.75		
4.0	6.0	4.4		
6.4	9.6	7.04		

Technical specification

- Structural Formation: BB-BG-OS & Y
- Driving Manner: Hand-Operated
- Driving Manner: Electric-Actuated
- Design Standard: DIN3352
- Face to Face: DIN3202
- Flange Ends: DIN2543-2547
- Test & Inspection: DIN3230

○ Notes: The size of serial, valve connecting flange can be design according to customers' requirement.



Main part material of Cast steel

Body	GS-C25						
Wedge Disc	GS-C25			1.4308		1.4408	
Stem	13Cr			1.4308		1.4408	
Wedge Disc Sealing Face	13Cr	13Cr	STL	1.4308	STL	1.4408	STL
Seat Ring Sealing Face	13Cr	STL	STL	1.4308	STL	1.4408	STL

Main part material of Stainless steel

Body	1.4308			1.4408			1.4306			1.4301		
Wedge Disc	1.4308			1.4408			1.4306			1.4301		
Stem	F304			1.4408			1.4306			1.4301		
Wedge Disc Sealing Face	1.4308	1.4308	STL	1.4408	1.4408	STL	1.4306	1.4306	STL	1.4301	1.4301	STL
Seat Ring Sealing Face	1.4308	STL	STL	1.4408	STL	STL	1.4306	STL	STL	1.4301	STL	STL

DIN Gate Valve



Size main dimensions of Gate Valve

Pressure (MPa)		PN1.6MPa													
Size	mm	50	65	80	100	125	150	200	250	300	350	400	450	500	600
L		250	270	280	300	325	350	400	450	500	550	600	650	700	800
H		417	452	530	607	720	790	885	1014	1190	1350	1460	1630	1800	2200
W		200	280	280	300	350	350	400	450	500	600	600	650	700	800
Weight(kg)		16	25	30	55	75	98	150	245	353	490	750	985	1063	1390
Pressure (MPa)		PN2.5MPa													
Size	mm	50	65	80	100	125	150	200	250	300	350	400	450	500	600
L		250	270	280	300	325	350	400	450	500	550	600	650	700	800
H		417	452	530	607	720	790	885	1014	1190	1350	1460	1630	1800	2200
W		200	280	280	300	350	350	400	450	500	600	600	650	700	800
Weight(kg)		16	31	43	58	82	103	180	265	385	547	835	1050	1130	1500
Pressure (MPa)		PN4.0MPa													
Size	mm	50	65	80	100	125	150	200	250	300	350	400	450	500	600
L		250	290	310	350	400	450	550	650	750	850	950	1050	1150	1350
H		404	456	604	607	720	780	875	1260	1480	1605	1788	1956	2168	2601
W		200	280	300	350	350	400	450	500	500	600	650	700	700	800
Weight(kg)		18	32	47	60	95	130	220	290	490	760	900	1250	1450	1700
Pressure (MPa)		PN6.4MPa													
Size	mm	50	65	80	100	125	150	200	250	300	350	400	450	500	600
L		250	290	310	350	400	450	550	650	750	850	950	1050	1150	1350
H		404	456	604	607	720	780	875	1260	1480	1605	1788	1956	2168	2601
W		200	280	300	350	350	400	450	500	500	600	650	700	700	800
Weight(kg)		20	35	52	66	103	140	230	300	510	780	940	1300	1600	1850

API SERIES

DIN SERIES

JIS SERIES

DIN Globe Valve



Product structural features

Globe valve seal acc. to DIN is applicable to the cutting and connection of pipelines medium that are used in various industries such as petroleum, chemical industry, pharmacy, chemical fertilizer, electric power industry etc under nominal pressure of PN1.6~16MPa and working temperature within -110~600℃

Main structural features

1. This product has logical structure, reliable seal, excellent performance and nice design.
2. The seal surface is build-up welding with Co hard alloy, which is attrition-resistant, corrosion-resistant, has good friction resistant and long life.
3. The stem quenched and tempered, and its surface is treated by nitrating treatment, thus it has good corrosion resistant and friction resistant.
4. The part material, flange and butt weld end dimension may be selected according to current operating condition and users' requirement, so that meeting the requirements of various engineering.

Technical specification

Structural Formation: BB-BG-OS & Y
Driving Manner: Hand-Operated
Driving Manner: Electric-Actuated
Design Standard: DIN3356
Face to Face: DIN3202
Flange Ends: DIN2543-2545
Test & Inspection: DIN3230

Notes: The size of serial, valve connecting flange can be design according to customers' requirement

Products performance specification


Nominal Pressure (MPa)	Shell Test (MPa)	Sealing Test (MPa)	Suitable Temp(℃)	Suitable Medium
1.6	2.4	1.76	-110~600℃	Water Oil & Gas
2.5	3.75	2.75		
4.0	6.0	4.4		
6.4	9.6	7.04		

DIN Globe Valve

Technical specification

- ◎ Structural Formation: BB-BG-OS & Y
- ◎ Driving Manner: Hand-Operated
- ◎ Driving Manner: Electric-Actuated
- ◎ Design Standard: DIN3356
- ◎ Face to Face: DIN3202
- ◎ Flange Ends: DIN2543-2545
- ◎ Test & Inspection: DIN3230

◎ Notes: The size of serial, valve connecting flange can be design according to customers' requirement.



Main part material of Cast steel

Body	GS-C25						
Disc	GS-C25		1.4308		1.4408		
Stem	13Cr		1.4308		1.4408		
Disc Sealing Face	13Cr	13Cr	STL	1.4308	STL	1.4408	STL
Seat Ring Sealing Face	13Cr	STL	STL	1.4308	STL	1.4408	STL

Main part material of Stainless steel

Body	1.4308			1.4408			1.4306			1.4301		
Disc												
Stem	F304			1.4408			1.4306			1.4301		
Wedge Disc Sealing Face	1.4308	1.4308	STL	1.4408	1.4408	STL	1.4306	1.4306	STL	1.4301	1.4301	STL
Ring Sealing Face	1.4308	STL	STL	1.4408	STL	STL	1.4306	STL	STL	1.4301	STL	STL

API SERIES

DIN SERIES

JIS SERIES

DIN Globe Valve



API SERIES

DIN SERIES

JIS SERIES

Size main dimensions of Globe Valve

Pressure(MPa)		PN1.6MPa															
Size	mm	15	20	25	32	40	50	65	80	100	125	150	200	250	300	350	400
L		130	150	160	180	200	230	290	310	350	400	480	600	650	750	850	950
H		240	260	276	285	300	305	354	402	437	496	541	699	815	914	1189	1350
W		120	140	160	160	180	200	200	750	250	300	350	400	450	500	550	600
Weight(kg)		5.2	7.1	7.4	8.5	13	20	25	35	50	75	100	210	446	648	805	1050
Pressure(MPa)		PN2.5MPa															
Size	mm	15	20	25	32	40	50	65	80	100	125	150	200	250	300	350	400
L		130	150	160	180	200	230	290	310	350	400	480	600	650	750	850	950
H		240	260	276	285	300	325	363	415	453	505	556	744	864	948	1269	1450
W		120	140	160	160	180	200	200	250	300	350	400	450	500	550	600	600
Weight(kg)		6	7.5	8	9	14	22	27	38	55	82	105	220	450	660	810	1100
Pressure(MPa)		PN4.0MPa															
Size	mm	15	20	25	32	40	50	65	80	100	125	150	200	250	300	350	400
L		130	150	160	180	200	230	290	310	350	400	480	600	650	750	850	950
H		240	260	276	285	300	325	370	430	480	532	589	783	888	965	1285	1512
W		120	140	160	160	180	200	200	250	300	350	400	450	500	550	600	600
Weight(kg)		6	7.5	8	9	15	24	30	41	60	85	110	225	460	670	830	1120
Pressure(MPa)		PN6.4MPa															
Size	mm	40	50	65	80	100	125	150	200	250	300	350	400				
L		260	300	340	380	430	500	550	650	775	900	1025	1150				
H		300	305	354	402	437	496	541	699	815	914	1189	1350				
W		180	200	200	750	250	300	350	400	450	500	550	600				
Weight(kg)		17	26	33	45	65	90	120	230	470	680	850	1130				
Pressure(MPa)		PN10.0MPa															
Size	mm	40	50	65	80	100	125	150	200	250	300	350	400				
L		260	300	340	380	450	500	550	650	775	900	1025	1150				
H		300	325	363	415	453	505	556	744	864	948	1269	1450				
W		180	200	200	250	300	350	400	450	500	550	600	600				
Weight(kg)		19	27	34	46	67	95	125	235	480	690	860	1150				

You are center of our world

DIN Check Valve



Product structural features

Check valve seal acc. to DIN is applicable to the cutting and connection of pipelines medium that are used in various industries such as petroleum, chemical industry, pharmacy, chemical fertilizer, electric power industry, etc under nominal pressure of PN1.6~16MPa, and working temperature within -110~600℃

Main structural features

1. This product has logical structure, reliable seal, excellent performance and nice design.
2. The seal surface is build-up welding with Co hard alloy, which is attrition-resistant, corrosion-resistant, has good friction resistant and long life.
3. The part material, flange and butt weld end dimension may be selected according to current operating condition and users' requirement, so that meeting the requirements of various engineering.

Technical specification

Structural Formation: BB-BG-OS & Y
Driving Manner: Hand-Operated
Driving Manner: Electric-Actuated
Design Standard: DIN3356
Face to Face: DIN3202
Flange Ends: DIN2543-2545
Test & Inspection: DIN3230

Notes: The size of serial, valve connecting flange can be design according to customers' requirement


Product Performance Specification

Nominal Pressure (MPa)	Shell Test (MPa)	Sealing Test (MPa)	Suitable Temp (°C)	Suitable Medium
1.6	2.4	1.76	-110~600℃	Water Oil & Gas
2.5	3.75	2.75		
4.0	6.0	4.4		
6.4	9.6	7.04		

Technical specification

- Structural Formation: BB-BG-OS & Y
- Driving Manner: Wc-Co Hand-Operated
- Driving Manner: Electric-Actuated
- Design Standard: DIN3356
- Face to Face: DIN3202
- Flange Ends: DIN2543-2547
- Test & Inspection: DIN3230

● Notes: The size of serial, valve connecting flange can be design according to customers' requirement.




Wedge Disc Check Valve Construction

Body	GS-C25						
Cover	GS-C25			1.4308		1.4408	
Disc Sealing Face	13Cr	13Cr	STL	1.4308	STL	1.4408	STL
Seat Ring Sealing Face	13Cr	STL	STL	1.4308	STL	1.4408	STL

Wedge Disc Check Valve Construction

Body	1.4308			1.4408			1.4306			1.4301		
Cover	1.4308			1.4408			1.4306			1.4301		
Wedge Disc Sealing Face	1.4308	1.4308	STL	1.4408	1.4408	STL	1.4306	1.4306	STL	1.4301	1.4301	STL
Seat Ring Sealing Face	1.4308	STL	STL	1.4408	STL	STL	1.4306	STL	STL	1.4301	STL	STL

DIN Swing Check Valve



Size main dimensions of Swing Check Valve


Pressure(MPa)		PN1.6MPa											
Size	mm	50	65	80	100	125	150	200	250	300	350	400	
L		230	290	310	350	400	480	550	650	750	850	950	
H		305	354	402	437	496	541	699	815	914	1189	1350	
Weight(kg)		21	28	38	58	92	130	210	295	365	410	460	
Pressure(MPa)		PN2.5MPa											
Size	mm	50	65	80	100	125	150	200	250	300	350	400	
L		230	290	310	350	400	480	550	650	750	850	950	
H		325	363	415	453	505	556	744	864	948	1269	1450	
Weight(kg)		22	29	38	61	96	132	213	297	375	415	480	
Pressure(MPa)		PN4.0MPa											
Size	mm	50	65	80	100	125	150	200	250	300	350	400	
L		230	290	310	350	400	480	550	650	750	850	950	
H		325	370	430	480	532	589	783	888	965	1285	1512	
Weight(kg)		22	31	41.5	65	100	136	220	305	400	450	510	
Pressure(MPa)		PN6.4MPa											
Size	mm	50	65	80	100	125	150	200	250	300	350	400	
L		300	340	380	430	500	550	650	775	900	1025	1150	
H		305	354	402	437	496	541	699	815	914	1189	1350	
Weight(kg)		27	37	57	87	135	184	266	396	643	815	1230	
Pressure(MPa)		PN10.0MPa											
Size	mm	50	65	80	100	125	150	200	250	300	350	400	
L		300	340	380	430	500	550	650	775	900	1025	1150	
H		325	363	415	453	505	556	744	864	948	1269	1450	
Weight(kg)		30	40	60	92	140	195	280	406	670	850	1260	

API SERIES

DIN SERIES

JIS SERIES

DIN Lift Check Valve



API SERIES

DIN SERIES

JIS SERIES

Size main dimensions of Lift Check Valve

Pressure(MPa)		PN1.6MPa										
Size	mm	50	65	80	100	125	150	200	250	300	350	400
L		230	290	310	350	400	480	600	650	750	850	950
H		305	354	402	437	496	541	699	815	914	1189	1350
Weight(kg)		10	20	30	39	50	70	161	251	395	500	618
Pressure(MPa)		PN2.5MPa										
Size	mm	50	65	80	100	125	150	200	250	300	350	400
L		230	290	310	350	400	480	600	650	750	850	950
H		325	363	415	453	505	556	744	864	948	1269	1450
Weight(kg)		12	22	33	44	55	78	180	270	410	520	650
Pressure(MPa)		PN4.0MPa										
Size	mm	50	65	80	100	125	150	200	250	300	350	400
L		230	290	310	350	400	480	600	650	750	850	950
H		325	370	430	480	532	589	783	888	965	1285	1512
Weight(kg)		13	23	34	46	60	85	190	280	430	550	680

You are center of our world

DIN Ball Valve



Product structural features

Ball valve seal acc. to DIN is applicable to the cutting and connection of pipelines medium that are used in various industries such as petroleum, chemical industry, pharmacy, chemical fertilizer, electric power industry etc under nominal pressure of PN1.6~10MPa and working temperature within -196~150°C.

Main structural features

1. The product has indication of open-close and locking system;
2. The stem has function of anti-blow out, anti fire-safe and anti-static function;
3. The part material flange, and butting weld end dimension may be selected according to current operation condition and user's requirement, so that meeting the requirement of various engineering.

Technical specification


Structural Formation: BB-BG-OS & Y
Driving Manner: Hand-Operated
Driving Manner: Electric-Actuated
Design Standard: DIN3356
Face to Face: DIN3202
Flange Ends: DIN2543-2545
Test & Inspection: DIN3230

Notes: The size of serial, valve connecting flange can be design according to customers' requirement

PERFORMANCE SPECIFICATION

Nominal Pressure (MPa)	Shell Test (MPa)	Sealing Test (MPa)	Suitable Temp(°C)	Suitable Medium
1.6	2.4	1.76	-196~150°C	Water Oil & Gas
2.5	3.75	2.75		
4.0	6.0	4.4		
6.4	9.6	7.04		
10.0	10.5	11		

DIN Floating Ball Valve



Size dimensions of DIN Floating Ball Valve

PN 16

DN	15	20	25	32	40	50	65	80	100	125	150	200
L	130	140	150	165	180	200	220	250	280	320	360	400
H	78	84	95	150	150	190	195	215	250	285	330	370
H1	140	160	180	250	300	350	350	400	600	600	800	1000
Wt(Kg)	3	4	5	10	14	20	25	30	40	65	73	85

PN 25

DN	15	20	25	32	40	50	65	80	100	125	150	200
L	130	140	150	165	180	200	220	250	280	320	360	400
H	78	84	95	150	150	190	195	215	250	285	330	370
H1	140	160	180	250	300	350	350	400	600	600	800	1000
Wt(Kg)	3	4	5	10	14	20	25	30	40	65	73	85

PN 40


DN	15	20	25	32	40	50	65	80	100	125	150	200
L	130	140	150	165	180	200	220	250	280	403	403	502
H	82	100	104	150	150	190	195	215	250	260	275	335
H1	140	160	180	250	300	350	350	400	600	600	800	800
Wt(Kg)	3	4	5	10	14	20	25	50	70	80	85	101

API SERIES

DIN SERIES

JIS SERIES

DIN Trunnion Ball Valve



Size and Dimensions of Trunnion Ball Valve

PN 16/25

DN	50	65	80	100	125	150	200	250	300	350	400	450	500	600	700	800	900	1000
L RF	179	191	203	229	356	394	457	533	610	686	762	846	914	1067	1245	1372	1524	1753
L BW	216	241	283	305	381	457	521	559	635	762	838	914	991	1143	1346	1524	1727	1880
H	107	125	152	178	300	330	398	495	580	625	670	698	840	1050	1100	1150	1247	1374
H1	102	114	127	152	184	219	273	360	395	430	470	550	580	700	800	950	1100	1200
W	230	400	400	650	1050	105	600	600	800	800	800	800	800	800	800	800	800	800
Wt(Kg)	12	16	22	35	58	74	205	322	460	576	864	1280	1600	3540	4500	5940	7540	9320

PN 40

DN	50	65	80	100	125	150	200	250	300	350	400	450	500	600	700	800	900	1000
L RF	216	241	283	305	381	403	502	568	648	762	838	914	991	1143	1346	1524	1727	1880
L BW	216	241	283	305	381	457	521	559	635	762	838	914	991	1143	1346	1524	1727	1880
H	107	125	152	178	300	330	398	495	580	625	670	698	840	1050	1100	1150	1247	1374
H1	102	114	127	152	184	219	273	360	395	430	470	550	580	700	800	950	1100	1200
W	230	400	400	650	1050	1050	600	600	800	800	800	800	800	800	800	800	800	800
Wt(Kg)	15	24	30	55	87	118	255	370	533	640	1030	1542	2100	4200	5300	7860	8684	10300

PN 64

DN	50	65	80	100	150	200	250	300	350	400	500	600	700					
L RF	292	330	356	406	495	597	673	762	826	902	1054	1232	1397					
H	108	155	197	235	300	374	445	512	550	615	810	1010	1180					
H1	114	124	133	159	250	294	395	445	500	530	660	800	900					
W	600	600	600	600	600	800	800	800	800	800	800	800	800					
Wt(Kg)	23	35	49	91	192	355	640	880	1100	1540	2800	5300	5700					



PN 100

DN	50	65	80	100	150	200	250	300	350	400	500	600	700					
L RF	292	330	356	432	559	660	787	838	889	991	1194	1397	1579					
H	108	155	197	235	300	374	445	512	550	615	810	1010	1180					
H1	114	124	133	159	250	294	395	445	500	530	660	800	900					
W	600	600	600	600	600	800	800	800	800	800	800	800	800					
Wt(Kg)	23	38	55	102	232	290	710	960	1700	1970	3250	5800	6700					

JIS Valve Series



JIS Gate Valve



Parts and material list

Parts name	Material				
	WCB/Trim 1	WCB/Trim 5	WCB/Trim 8	CF8/304	CF8M/316
Body	ASTM A216 WCB	ASTM A216 WCB	ASTM A216 WCB	ASTM A351 CF8	ASTM A351 CF8M
Seat ring	A105+13Cr	A105+STL	A105+STL	ASTM A351 CF8	ASTM A351 CF8M
Gate	ASTMA216WCB+13Cr	ASTMA216 WCB+STL	ASTMA216 WCB+13Cr	ASTM A351 CF8	ASTM A351 CF8M
Stem	ASTM A182 F6a	ASTM A182 F6a	ASTM A182 F6a	ASTM A182 F304	ASTM A182 F316
Bonnet bolt	ASTM A193 B7	ASTM A193 B7	ASTM A193 B7	ASTM A193 B8	ASTM A193 B8M
Bonnet nut	ASTM A194 2H	ASTM A194 2H	ASTM A194 2H	ASTM A194 8	ASTM A194 8M
Gasket	304 + Graphite			304 + Graphite	316 + Graphite
Bonnet	ASTM A216 WCB	ASTM A216 WCB	ASTM A216 WCB	ASTM A351 CF8	ASTM A351 CF8M
Backseat bushing	ASTM A182 F6a	ASTM A182 F6a	ASTM A182 F6a	ASTM A351 CF8	ASTM A351 CF8M
Packing	Graphite	Graphite	Graphite	Graphite	Graphite
Gland eyebolt	ASTM A193 B7	ASTM A193 B7	ASTM A193 B7	ASTM A193 B8	ASTM A193 B8M
Eyebolt nut	ASTM A194 2H	ASTM A194 2H	ASTM A194 2H	ASTM A194 8	ASTM A194 8M
Eyebolt pin	ASTM AISI 1045	ASTM AISI 1045	ASTM AISI 1045	304ss	316ss
Gland	ASTM A182 F6a	ASTM A182 F6a	ASTM A182 F6a	ASTM A182 F304	ASTM A182 F316
Gland flange	ASTM A216 WCB	ASTM A216 WCB	ASTM A216 WCB	ASTM A351 CF8	ASTM A351 CF8M
Stem nut	Copper alloy	Copper alloy	Copper alloy	Copper alloy	Copper alloy
Nipple	Carbon steel	Carbon steel	Carbon steel	Carbon steel	Carbon steel
Yoke sleeve nut	Carbon steel	Carbon steel	Carbon steel	Carbon steel	Carbon steel
Hand wheel	Carbon steel	Carbon steel	Carbon steel	Carbon steel	Carbon steel
Hand wheel nut	Carbon steel	Carbon steel	Carbon steel	Carbon steel	Carbon steel

Note: The chart above only lists out some common composition of steel gate valve parts. We may provide other different parts material composition according to the customer's request or the actual valve working condition.

API SERIES

DIN SERIES

JIS SERIES

Features

Our company JIS gate valve usually be reliably used in steam, air, coat gas, oil or oil gas etc high or low-pressure condition. Middle or low-pressure valve normal valve normal adopt taper disc seating structure, but the large diameter and high pressure valve adopt sideway disc sealing structure, the medium flow from high to low position, it use medium self pressure seal, so the sealing is very reliable and the operated torque is more light. According to condition, the valve can be apply more kinds of material and connection type between bonnet and body and can be reach to more requirements of user.

Construction as follows

1. Full Bore/Reduce bore
2. Outside screw stem and rising Yoke
3. Detachable seat and Back-seat
4. Two piece self aligning packing gland

Standard				
Design And Manufacture	Face To Face	Flange Dimension	Pressure-Temperture rating	Inspection And Test
JIS B2071 B2081	JIS B2002	JIS B2212 B2214	JIS B2071 B2081	JIS B2003

Capability criterion							
Body material	SPCH2-11	SPCH2-32	SCS13A	SCS19A	SCS14A	SCS16A	SCPL1
Suitable Temperature	≤425°C	≤540°C	≤275°C	≤200°C	≤275°C	≤200°C	-45~150°C
Appropriate Medium	Water Steam Oil Goods		Nitric Acid		Acetic Acid		Liquid Ammonia

Size main dimensions of Gate Valve									
DN		10K							
mm	in	L	D	D1	D2	b	n-φ d	H	D0
15	1/2	108	95	70	52	12	4-φ 15	179	100
20	3/4	117	100	75	58	14	4-φ 15	198	100
25	1	127	125	90	70	14	4-φ 19	255	130
40	1 1/2	165	140	105	85	16	4-φ 19	323	160
50	2	178	155	120	100	16	4-φ 19	409	160
65	2 1/2	190	175	140	120	18	4-φ 19	535	250
80	3	203	185	150	130	18	8-φ 19	570	250
100	4	229	210	175	155	18	8-φ 19	590	250
125	5	250	210	185	185	2	8-φ 23	605	280
150	6	267	280	240	215	22	8-φ 23	630	300
200	8	292	330	290	265	22	12-φ 23	960	350
250	10	330	400	355	325	24	12-φ 25	1158	400
300	12	356	445	400	370	24	16-φ 25	1378	450
350	14	381	490	445	415	26	16-φ 25	1543	500
400	16	406	560	510	475	28	16-φ 27	1738	600
450	18	432	620	565	530	30	20-φ 27	1959	600
500	20	457	675	620	585	30	20-φ 27	2214	680

Size main dimensions of Gate Valve

DN		20K							
mm	in	L	D	D1	D2	b	n-φ d	H	D0
15	1/2	140	95	70	52	14	4-15	179	130
20	3/4	152	100	75	58	16	4-15	202	130
25	1	165	125	90	70	16	4-19	265	160
40	1 1/2	190	140	105	85	18	4-19	415	200
50	2	216	155	120	100	18	8-φ 19	480	200
65	2 1/2	241	175	140	120	20	8-φ 19	510	250
80	3	283	200	160	135	22	8-φ 23	580	280
100	4	305	225	185	160	24	8-φ 23	700	350
125	5	381	270	225	195	26	8-25	845	400
150	6	403	305	260	230	28	12-φ 25	940	400
200	8	419	350	305	275	30	12-φ 25	1190	450
250	10	457	430	380	345	34	12-φ 27	1390	500
300	12	502	480	430	395	35	16-φ 27	1600	500
350	14	762	540	480	440	40	16-φ 33	1750	600
400	16	838	605	540	495	46	16-φ 33	1900	600
450	18	914	675	605	560	48	20-φ 33	2320	650
DN		40K							
mm	in	L	D	D1	D2	b	n-φ d	H	D0
15	1/2	165	115	80	55	20	4-φ 19	179	160
20	3/4	190	120	85	60	20	4-φ 19	202	200
25	1	216	130	95	70	22	4-φ 19	265	200
40	1 1/2	241	160	120	90	24	4-φ 23	415	200
50	2	292	165	130	105	26	8-φ 19	480	280
65	2 1/2	330	200	160	130	30	8-23	510	280
80	3	356	210	170	140	32	8-23	580	300
100	4	432	250	205	165	36	8-25	700	400
125	5	508	300	250	200	40	8-27	845	500
150	6	559	355	295	240	44	12-33	940	500
200	8	660	405	345	290	50	12-33	1190	500
250	10	787	475	410	355	56	12-33	1390	600
300	12	838	540	470	410	60	16-39	1600	650
350	14	889	585	515	455	64	16-39	1750	650
400	16	991	645	570	515	70	16-39	1900	700

API SERIES

DIN SERIES

JIS SERIES




Figure 1: JIS Globe Valve (1/4")

Parts name	Material				
	WCB/Trim 1	WCB/Trim 5	WCB/Trim 8	CF8/304	CF8M/316
Body	ASTM A216 WCB+13Cr	ASTM A216 WCB+STL	ASTM A216 WCB+STL	ASTM A351 CF8	ASTM A351 CF8M
Disc	ASTM A216 WCB+13Cr	ASTM A216 WCB+STL	ASTM A216 WCB+13Cr	ASTM A351 CF8	ASTM A351 CF8M
Stem	ASTM A182 F6a	ASTM A182 F6a	ASTM A182 F6a	ASTM A182 F304	ASTM A182 F316
Disc nut	ASTM A216 WCB	ASTM A216 WCB	ASTM A216 WCB	ASTM A351 CF8	ASTM A351 CF8M
Bonnet nut	ASTM A194 2H	ASTM A194 2H	ASTM A194 2H	ASTM A194 8	ASTM A194 8M
Bonnet bolt	ASTM A193 B7	ASTM A193 B7	ASTM A193 B7	ASTM A193 B8	ASTM A193 B8M
Gasket	304+Graphite	304+Graphite	304+Graphite	304 + Graphite	316 + Graphite
Backseat bushing	ASTM A182 F6a	ASTM A182 F6a	ASTM A182 F6a	ASTM A351 CF8	ASTM A351 CF8M
Bonnet	ASTM A216 WCB	ASTM A216 WCB	ASTM A216 WCB	ASTM A351 CF8	ASTM A351 CF8M
Packing	Graphite	Graphite	Graphite	Graphite	Graphite
Eyebolt pin	ASTM AISI 1045	ASTM AISI 1045	ASTM AISI 1045	304ss	316ss
Gland eyebolt	ASTM A193 B7	ASTM A193 B7	ASTM A193 B7	ASTM A193 B8	ASTM A193 B8M
Gland	ASTM A182 F6a	ASTM A182 F6a	ASTM A182 F6a	ASTM A182 F304	ASTM A182 F316
Gland flange	ASTM A216 WCB	ASTM A216 WCB	ASTM A216 WCB	ASTM A351 CF8	ASTM A351 CF8M
Eyebolt nut	ASTM A194 2H	ASTM A194 2H	ASTM A194 2H	ASTM A194 8	ASTM A194 8M
Stem nut	Copper alloy	Copper alloy	Copper alloy	Copper alloy	Copper alloy
Hand wheel	Carbon steel	Carbon steel	Carbon steel	Carbon steel	Carbon steel
Hand wheel nut	Carbon steel	Carbon steel	Carbon steel	Carbon steel	Carbon steel

Features

Our company JIS globe valve usually be reliably used in steam, air, coat gas, oil or oil gas etc high or low-pressure condition. Middle or low-pressure valve normal valve normal adopt taper disc seating structure, but the large diameter and high pressure valve adopt sideways disc sealing structure, the medium flow from high to low position, it use medium self pressure seal, so the sealing is very reliable and the operated torque is more light. According to condition, the valve can be apply more kinds of material and connection type between bonnet and body and can be reach to more requirements of user .

Construction as follows

1. Full Bore/Reduce bore
2. Outside screw and Yoke, rising stem
3. Integral seat and Detachable Back-seat
4. Bolted Bonnet/Pressure seal Bonnet
5. Tow piece self-aligning packing gland

Standard				
Design And Manufacture	Face To Face	Flange Dimension	Pressure-Temperature rating	Inspection And Test
JIS B2071 B2081	JIS B2002	JIS B2212 B2214	JIS B2071 B2081	JIS B2003

Capability criterion							
Body material	SPCH2-11	SPCH2-32	SCS13A	SCS19A	SCS14A	SCS16A	SCPL1
Suitable Temperature	≤425℃	≤540℃	≤275℃	≤200℃	≤275℃	≤200℃	-45~150℃
Appropriate Medium	Water Steam Oil Goods		Nitric Acid		Acetic Acid		Liquid Ammonia

Size main dimensions of Globe Valve									
DN		10K							
mm	in	L	D	D1	D2	b	n-φd	H	D0
15	1/2	108	95	70	52	12	4-φ15	241	100
20	3/4	117	100	75	58	14	4-φ15	241	100
25	1	127	125	90	70	14	4-φ19	242	130
40	1 1/2	1165	140	105	85	16	4-φ19	286	160
50	2	203	155	120	100	16	4-φ19	360	200
65	2 1/2	216	175	140	120	18	4-φ19	380	200
80	3	241	185	150	130	18	8-φ19	415	250
100	4	292	210	175	155	18	8-φ19	465	250
125	5	356	250	210	185	20	8-φ23	515	300
150	6	406	280	240	215	22	8-φ23	545	350
200	8	495	330	290	265	22	12-φ23	675	450
250	10	622	400	355	325	24	12-φ25	787	600
300	12	698	445	400	370	24	16-φ25	895	650


JIS Globe Valve



Size main dimensions of Globe Valve

DN		20K							
mm	in	L	D	D1	D2	b	n-φ d	H	D0
15	1/2	152	95	70	52	14	4-15	259	130
20	3/4	178	100	75	58	16	4-15	281	160
25	1	203	125	90	70	16	4-19	315	200
40	1 1/2	229	140	105	85	18	4-19	356	200
50	2	267	155	120	100	18	8-φ 19	420	200
65	2 1/2	292	175	140	120	20	8-φ 19	465	250
80	3	318	200	160	135	22	8-φ 23	490	300
100	4	356	225	185	160	24	8-φ 23	590	350
125	5	400	270	225	195	26	8-φ 25	690	400
150	6	444	305	260	230	28	12-φ 25	760	450
200	8	559	350	305	275	30	12-φ 25		450
250	10	622	430	380	345	34	12-27	787	600
300	12	711	480	430	395	35	16-27	895	650
DN		40K							
mm	in	L	D	D1	D2	b	n-φ d	H	D0
15	1/2	165	115	80	55	20	4-19	259	160
20	3/4	190	120	85	60	20	4-19	281	160
25	1	216	130	95	70	22	4-19	315	200
40	1 1/2	241	160	120	90	24	4-23	356	230
50	2	292	165	130	105	26	8-19	420	280
65	2 1/2	330	200	160	130	30	8-23	465	280
80	3	356	210	170	140	32	8-23	490	300
100	4	432	250	205	165	36	8-25	590	400
125	5	508	300	250	200	40	8-27	690	400
150	6	559	355	295	240	44	12-33	760	500
200	8	660	405	345	290	50	12-33	920	500
250	10	787	475	410	355	56	12-33	1080	600
300	12	838	540	470	410	60	16-39	1270	650
350	14	889	585	515	455	64	16-39	1420	650
400	16	991	645	570	515	70	16-39	1600	700

JIS Check Valve



API SERIES

DIN SERIES

JIS SERIES

Parts and material list

Parts name	Material				
	WCB/Trim 1	WCB/Trim 5	WCB/Trim 8	CF8/304	CF8M/316
Body	ASTM A216 WCB	ASTM A216 WCB	ASTM A216 WCB	ASTM A351 CF8	ASTM A351 CF8M
Seat ring	A105+13Cr	A105+STL	A105+STL	ASTM A351 CF8	ASTM A351 CF8M
Disc	ASTM A216 WCB+13Cr	ASTM A216 WCB+STL	ASTM A216 WCB+13Cr	ASTM A351 CF8	ASTM A351 CF8M
Arm	ASTM A216 WCB	ASTM A216 WCB	ASTM A216 WCB	ASTM A351 CF8	ASTM A351 CF8M
Nut	ASTM A194 2H	ASTM A194 2H	ASTM A194 2H	ASTM A194 8	ASTM A194 8M
Arm pin	ASTM A182 F6a	ASTM A182 F6a	ASTM A182 F6a	ASTM A182 F304	ASTM A182 F316
Yoke	ASTM A216 WCB	ASTM A216 WCB	ASTM A216 WCB	ASTM A351 CF8	ASTM A351 CF8M
Bonnet nut	ASTM A194 2H	ASTM A194 2H	ASTM A194 2H	ASTM A194 8	ASTM A194 8M
Bonnet bolt	ASTM A193 B7	ASTM A193 B7	ASTM A193 B7	ASTM A193 B8	ASTM A193 B8M
Bolt	ASTM A193 B7	ASTM A193 B7	ASTM A193 B7	ASTM A193 B8	ASTM A193 B8M
Gasket	304+Graphite	304+Graphite	304+Graphite	304+Graphite	316+Graphite
Bonnet	ASTM A216 WCB	ASTM A216 WCB	ASTM A216 WCB	ASTM A351 CF8	ASTM A351 CF8M
Eye bolt	ASTM A181	ASTM A181	ASTM A181	ASTM A181	ASTM A181

Note: The chart above only lists out some common composition of steel check valve parts. We may provide other different parts material composition according to the customer's request or the actual valve working condition.

Features

Our company JIS check valve usually be reliably used in steam, air, coal pas, oil or oil gas etc high or low -pressure condition. High or low-pressure valve normal adopt internal rocker to reduce medium external leakage. It can be equipped external lever and adjusting foundry weight and can be select connection type and trim material according to working condition if user need. Large check valve usually be equipped with vibration absorber.

Construction as follows

1. Full Bore/Reduce bore
2. Rising disc/swing desc
3. Detachable seat
4. Bolted cover/Pressure seal cover

Standard				
Design And Manufacture	Face To Face	Flange Dimension	Pressure-Temperature rating	Inspection And Test
JIS B2071 B2081	JIS B2002	JIS B2212 B2214	JIS B2071 B2081	JIS B2003

Capability criterion							
Body material	SPCH2-11	SPCH2-32	SCS13A	SCS19A	SCS14A	SCS16A	SCPL1
Suitable Temperature	≤425°C	≤540°C	≤275°C	≤200°C	≤275°C	≤200°C	-45~150°C
Appropriate Medium	Water Steam Oil Goods		Nitric Acid		Acetic Acid		Liquid Ammonia

Size main dimensions of Check Valve									
DN		10K							
mm	in	L	D	D1	D2	b	n-φ d	H	D0
15	1/2	108	95	70	52	12	4-15	79	79
20	3/4	117	100	75	58	14	4-15	79	79
25	1	127	125	90	70	14	4-19	110	110
40	1 1/2	165	140	105	85	16	4-19	154	154
50	2	203	155	120	100	16	4-φ 19	165	165
65	2 1/2	216	175	140	120	18	4-φ 19	175	175
80	3	241	185	150	130	18	8-φ 19	190	190
100	4	292	210	175	155	18	8-φ 19	215	215
125	5	330	250	210	185	20	8-φ 23	240	240
150	6	356	280	240	215	22	8-φ 23	265	265
200	8	495	330	290	265	22	12-φ 23	320	320
250	10	622	400	355	325	24	12-φ 25	365	365
300	12	698	445	400	370	24	16-φ 25	415	415
350	14	787	490	445	415	26	16-φ 25	460	460
400	16	864	560	510	475	28	16-φ 27	495	495
450	18	978	620	565	530	30	20-φ 27	550	550
500	20	978	675	620	585	30	20-φ 27	610	610
600	24	1295	795	730	690	32	24-φ 33	660	660
700	28	1448	905	840	800	34	24-φ 33	725	725
800	32	/	1020	950	905	36	28-φ 33	780	780
850	34	/	1070	1000	955	36	28-φ 33	835	835
900	36	1956	1120	1050	1005	38	28-φ 33	890	890

Size main dimensions of Check Valve


DN		20K							
mm	in	L	D	D1	D2	b	n-φ d	H	D0
15	1/2	152	95	70	52	14	4-φ 15	79	79
20	3/4	178	100	75	58	16	4-φ 15	110	110
25	1	216	125	90	70	16	4-φ 19	154	154
40	1 1/2	241	140	105	85	18	4-φ 19	165	165
50	2	267	155	120	100	18	8-φ 19	190	190
65	2 1/2	292	175	140	120	20	8-φ 19	205	205
80	3	318	200	160	135	22	8-φ 23	220	220
100	4	356	225	185	160	24	8-φ 23	245	245
125	5	400	270	225	195	26	8-φ 25	268	368
150	6	444	305	260	230	28	12-φ 25	295	295
200	8	533	350	305	275	30	12-φ 25	330	330
250	10	622	430	380	345	34	12-φ 27	420	420
300	12	711	480	430	395	35	16-φ 27	480	480
350	14	838	540	480	440	40	16-φ 33	535	535
400	16	864	605	540	495	46	16-φ 33	585	585
450	18	978	675	605	560	48	20-φ 33	615	615
500	20	1016	730	660	615	50	20-33	610	610
600	24	1346	845	770	720	54	24-39	660	660
700	28	1499	995	900	840	64	24-48	725	725
800	32	/	1140	1030	960	72	24-56	780	780
850	34	/	1200	1090	1020	74	24-56	835	835
900	36	2083	1250	1140	1070	76	28-56	890	890
DN		40K							
mm	in	L	D	D1	D2	b	n-φ d	H	D0
15	1/2	165	115	80	55	20	4-φ 19	110	110
20	3/4	190	120	85	60	20	4-φ 19	110	110
25	1	216	130	95	70	22	4-φ 19	165	165
40	1 1/2	241	160	120	90	24	4-φ 23	190	190
50	2	292	165	130	105	26	8-φ 19	205	205
65	2 1/2	330	200	160	130	30	8-φ 23	220	220
80	3	356	210	170	140	32	8-φ 23	245	245
100	4	432	250	205	165	36	8-φ 25	295	295
125	5	508	300	250	240	40	8-φ 27	300	300
150	6	559	355	295	200	44	12-φ 33	330	330
200	8	660	405	345	290	50	12-φ 33	420	420
250	10	787	475	410	355	56	12-φ 33	480	480
300	12	838	540	470	410	60	16-φ 39	535	535
350	14	889	585	515	455	64	16-φ 39	585	585
400	16	991	645	570	515	70	16-φ 39	615	615

API SERIES

DIN SERIES

JIS SERIES

JIS Ball Valve



Parts and material list

Parts name	Material				
	WCB/13Cr	WCB/304	WCB/316	CF8	CF8M
Body	ASTM A216 WCB	ASTM A216 WCB	ASTM A216 WCB	ASTM A351 CF8	ASTM A351 CF8M
Body nut	ASTM A194 2H	ASTM A194 2H	ASTM A194 2H	ASTM A194 8	ASTM A194 8M
Body bolting	ASTM A193 B7	ASTM A193 B7	ASTM A193 B7	ASTM A193 B8	ASTM A193 B8M
Gasket	PTFE	PTFE	PTFE	PTFE	PTFE
Cap	ASTM A216 WCB	ASTM A216 WCB	ASTM A216 WCB	ASTM A351 CF8	ASTM A351 CF8M
Ball	ASTM A182 F6a	ASTM A182 F304	ASTM A182 F316	ASTM A182 F304	ASTM A182 F316
Seat	Reinforced PTFE	Reinforced PTFE	Reinforced PTFE	Reinforced PTFE	Reinforced PTFE
Stem	ASTM A182 F6a	ASTM A182 F304	ASTM A182 F316	ASTM A182 F304	ASTM A182 F316
Packing	PTFE	PTFE	PTFE	PTFE	PTFE
Gland	ASTM A182 F6a	ASTM A182 F304	ASTM A182 F316	ASTM A182 F304	ASTM A182 F316
Gland flange	ASTM A216 WCB	ASTM A216 WCB	ASTM A216 WCB	ASTM A351 CF8	ASTM A351 CF8M
Gland bolt	ASTM A193 B7	ASTM A193 B7	ASTM A193 B7	ASTM A193 B8	ASTM A193 B8M
Stop collar	Carbon steel	Carbon steel	Carbon steel	Stainless steel	Stainless steel
Lever	Carbon steel	Carbon steel	Carbon steel	Carbon steel	Carbon steel

Note: The chart above only lists out some common composition of steel ball valve parts. We may provide other different parts material composition according to the customer's request or the actual valve working condition.

Features

Our company JIS ball valve is widely used in such fields as petroleum melting, chemical industry, papermaking, pharmaceutical industry, food industry, water power, electric power, city planning, steel. Among them the sulphur-resistance serial ball valve is especially applicable for Natural Gas Long-Distance Transportation features containing sulphuretted hydrogen medium, mang impurity and serious corroding .

Construction as follows

- | | |
|--|--|
| 1. Bolted bonnet, Two-piece Body, Floating Ball | 1. Bolted cover, Two-piece or three-piece Body, fixed Ball |
| 2. Full or Reduced bore, Blowout Proof Stem | 2. Full or Reduced bore, Blowout Proof Stem |
| 3. Fire safe and Anti static | 3. Fire safe and Anti static |
| 4. Stainless steel ball | 4. Dual seat with injection and drain & outlet |
| 5. ASTM A216 WCB, A351 CF8, A351 CF8M, A351 CF3, A351 CF3M | 5. ASTM A216 WCB, A351 CF8, A351 CF8M, A351 CF3, A351 CF3M |

Standard				
Design And Manufacture	Face To Face	Flange Dimension	Pressure-Temperature rating	Inspection And Test
JIS B2071 B2081	JIS B2002	JIS B2212 B2214	JIS B2071 B2081	JIS B2003

Capability criterion							
Body material	SPCH2-11	SPCH2-32	SCS13A	SCS19A	SCS14A	SCS16A	SCPL1
Suitable Temperature	≤425℃	≤540℃	≤275℃	≤200℃	≤275℃	≤200℃	-45~150℃
Appropriate Medium	Water Steam Oil Goods		Nitric Acid		Acetic Acid		Liquid Ammonia

Size main dimensions of Ball Valve									
DN		10K							
mm	in	L	D	D1	D2	b	n-φd	H	D0
15	1/2	108	95	70	52	12	4-φ15	59	130
20	3/4	117	100	75	58	14	4-φ15	63	130
25	1	127	125	90	70	14	4-φ19	75	160
40	1 1/2	165	140	105	85	16	4-φ19	95	230
50	2	178	155	120	100	16	4-φ19	107	230
65	2 1/2	190	175	140	120	18	4-φ19	142	400
80	3	203	185	150	130	18	8-φ19	152	400
100	4	229	210	175	155	18	8-φ19	178	700
125	5	356	250	210	185	20	8-φ23	252	1100
150	6	394	280	240	215	22	8-φ23	272	1100
200	8	457	330	290	265	22	12-φ23	342	1500
250	10	533	400	355	325	24	12-φ25	345	1500

Note: The chart above only lists out some common composition of steel globe valve parts. We may provide other different parts material composition according to the customer's request or the actual valve working condition.

JIS Ball Valve



API SERIES

DIN SERIES

JIS SERIES

Size main dimensions of Ball Valve


DN		20K							
mm	in	L	D	D1	D2	b	n-φ d	H	D0
15	1/2	140	95	70	52	14	4-φ 15	59	130
20	3/4	152	100	75	58	16	4-φ 15	63	130
25	1	165	125	90	70	16	4-φ 19	75	160
40	1 1/2	190	140	105	85	18	4-φ 19	95	230
50	2	216	155	120	100	18	8-φ 19	107	230
65	2 1/2	241	175	140	120	20	8-φ 19	142	400
80	3	283	200	160	135	22	8-φ 23	152	400
100	4	305	225	185	160	24	8-φ 23	178	700
125	5	381	270	225	195	26	8-φ 25	252	1100
150	6	403	305	260	230	28	12-φ 25	272	1100
200	8	502	350	305	275	30	12-φ 25	342	1500
250	10	568	430	380	345	34	12-φ 27	345	1500
DN		40K							
mm	in	L	D	D1	D2	b	n-φ d	H	D0
15	1/2	165	115	80	55	20	4-19	59	130
20	3/4	190	120	85	60	20	4-19	63	160
25	1	216	130	95	70	22	4-19	75	230
40	1 1/2	241	160	120	90	24	4-23	95	230
50	2	292	165	130	105	26	8-19	107	400
65	2 1/2	330	200	160	130	30	8-23	142	400
80	3	356	210	170	140	32	8-23	152	700
100	4	432	250	205	165	36	8-25	178	1100
125	5	508	300	250	200	40	8-27	252	1100
150	6	559	355	295	240	44	12-33	272	1100
200	8	660	405	345	290	50	12-33	342	1500
250	10	787	475	410	355	56	12-33	345	1500

You are center of our world

JIS Butterfly Valve



JIS wafer type, flanged type three eccentric hard sealing butterfly valve



◎ Purpose and characteristic

Main configuration characteristic of 10K and 20K series of butterfly valve is composed of wafer and flange three eccentric seal, seat gasket use two configurations of elastic seal and soft hard compatible multiple layers seal, reliable hermetic capability, so as to ensure disc can't touch sealing seat when it operation, solve the problem of sealing seat burden unequally, prolong service life, with advantage of high temperature resistant, wearable, antisepsis etc. It has been widely utilized in petroleum, chemical industry and industrial environmental protection water treatment, high building construction, water supplying and draining pipe etc.

Standard			
Design standard	Flange connection dimension	Structure length	Pressure test
API609-1983	JIS B2212, JIS B2213, JIS B2214	JIS B2002-1987	JIS B2003-1987

Main performance parameter					
Nominal diameter NPS(inch)	Nominal pressure PN(MPa)	Test pressure		Suitable medium	Suitable temperature
		Strength test	Seal test		
2"~48"	10K	1.5	1.1	Water, steam, oil seawater etc.	-29 ~ 550℃
2"~48"	20K	3.0	2.2		

Material for main parts	
Name	Material
Body	WCB' 304' 316' 316SS' CF8M
Disc	WCB' 304' 316' 316SS' CF8M
Stem	304' 316' 2Cr13' 1Cr18Ni9Ti
Seal ring	304' 316' Fluorine plastic
Packing	Flexible graphite, Fluorine plastic
Dirve mode	Handwheel, Worm gear, Air drive, Electric drive ect.

JIS Butterfly Valve



API SERIES

DIN SERIES

JIS SERIES

Wafer Butterfly Valve 10K~20K Series

Nominal diameter		Structure length (standard)	H	External dimension(consult)									Connection dimension (standard)			
				Worm Gear Driven			Pneumatic			Electric			10K		20K	
mm	inch	L		H1	A1	B1	H2	A2	B2	H3	A3	B3	D1	Z-d	D1	Z-d
50	2	43	112	350	180	200	625	245	72	530	250	255	120	4-19	120	8-19
65	2 1/2	46	115	370	180	200	625	245	72	530	250	255	140	4-19	140	8-19
80	3	49	120	380	180	200	645	245	72	565	250	255	150	8-19	160	8-23
100	4	56	138	420	180	200	675	355	92	600	250	255	175	8-19	185	8-23
125	5	64	164	460	180	200	715	355	92	640	250	255	210	8-23	225	8-25
150	6	70	175	555	270	280	800	355	92	705	300	315	240	8-23	260	12-25
200	8	71	208	605	270	280	850	250	170	775	300	315	290	12-23	305	12-25
250	10	76	243	680	270	280	925	250	170	945	300	315	355	12-25	380	12-27
300	12	83	283	800	380	420	1035	450	220	1070	300	315	400	16-25	430	16-27
350	14	92	310	835	380	420	1070	450	220	1140	300	315	445	16-25	480	16-33
400	16	102	340	915	450	470	1190	450	220	1210	300	315	510	16-27	540	16-33
450	18	114	380	960	480	490	1250	650	280	1335	575	714	565	20-27	605	20-33
500	20	127	410	1020	480	490	1290	650	280	1415	575	714	620	20-27	660	20-33
600	24	154	470	1225	480	490	1455	850	380	1605	656	810	730	24-33	770	24-39
700	28	165	550	1355	640	660	1585	850	380	1844	656	810	840	24-33	900	24-48
800	32	190	640	1470	640	660	1700	1250	380	2040	656	810	950	28-33	1030	24-56
900	36	203	710	1545	750	860	1965	1250	380	2255	785	863	1050	28-33	1140	28-56
1000	40	216	770	1795	850	900	2015	1250	380	2380	785	863	1160	28-39		
1200	48	254	890	1965	850	900	2250	1250	380	2640	785	863	1380	32-39		

Flanged Butterfly Valve 10K~20K Series

Nominal diameter		Structure length (standard)		H	External dimension(consult)									Connection dimension(standard)					
					Worm Gear Driven			Pneumatic			Electric			10K			20K		
mm	inch	Brief	Long		H1	A1	B1	H2	A2	B2	H3	A3	B3	D	D1	Z-d	D	D1	Z-d
50	2	108	150	112	350	180	200	605	245	72	530	250	255	155	120	4-19	155	120	8-19
65	2 1/2	112	170	115	370	180	200	625	245	72	530	250	255	175	140	4-19	175	140	8-19
80	3	114	180	120	380	180	200	645	245	72	565	250	255	185	150	8-19	200	160	8-23
100	4	127	190	138	420	180	200	675	355	92	600	250	255	210	175	8-19	225	185	8-23
125	5	140	200	164	460	180	200	715	355	92	640	250	255	250	210	8-23	270	225	8-25
150	6	140	210	175	555	270	280	800	355	92	705	300	315	280	240	8-23	305	260	12-25
200	8	152	230	208	605	270	280	850	250	170	775	300	315	330	290	12-23	350	305	12-25
250	10	165	250	243	680	270	280	925	250	170	945	300	315	400	355	12-25	430	380	12-27
300	12	178	270	283	800	380	420	1035	450	220	1070	300	315	445	400	16-25	480	430	16-27
350	14	190	290	310	835	380	420	1070	450	220	1140	300	315	490	445	16-25	540	480	16-33
400	16	216	310	340	915	450	470	1190	450	220	1210	300	315	560	510	16-27	605	540	16-33
450	18	222	330	380	960	480	490	1250	650	280	1335	575	714	620	565	20-27	675	605	20-33
500	20	229	350	410	1020	480	490	1290	650	280	1415	575	714	675	620	20-27	730	660	20-33
600	24	267	390	470	1225	480	490	1455	850	380	1605	656	810	795	730	24-33	845	770	24-39
700	28	292	430	550	1355	640	660	1585	850	380	1844	656	810	905	840	24-33	995	900	24-48
800	32	318	470	640	1470	640	660	1700	1250	380	2040	656	810	1020	950	28-33	1140	1030	24-56
900	36	330	510	710	1545	850	900	1865	1250	380	2255	785	863	1120	1050	28-33	1250	1140	28-56
1000	40	410	550	770	1795	850	900	2015	1500	580	2380	785	863	1235	1160	28-39			
1200	48	470	630	890	1965	850	900	2226	1500	580	2640	785	863	1465	1380	32-39			

Attention: Above two sorts such as wafer, flange, driving mode such as manual, worm wheel, pneumatic, and electric, user should specify when ordered.